

Title	Visualization and categorization of ecological acoustic events based on discriminant features
Authors	Huancapaza Hilasaca, Liz Maribel;Gaspar, Lucas Pacciullio;Ribeiro, Milton Cezar;Minghim, Rosane
Publication date	2021-01-26
Original Citation	Huancapaza Hilasaca, L. M., Gaspar, L. P., Ribeiro, M. C. and Minghim, R. (2021) 'Visualization and categorization of ecological acoustic events based on discriminant features', Ecological Indicators, 107316 (11 pp). doi: 10.1016/j.ecolind.2020.107316
Type of publication	Article (peer-reviewed)
Link to publisher's version	https://www.sciencedirect.com/science/article/pii/ S1470160X20312589 - 10.1016/j.ecolind.2020.107316
Rights	© 2021 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY license (http://creativecommons.org/licenses/by/4.0/) - http://creativecommons.org/licenses/by/4.0/
Download date	2024-04-20 13:01:14
Item downloaded from	https://hdl.handle.net/10468/11045



Supplementary material for visualization and categorization of ecological acoustic events based on discriminant features

March 27, 2020

1. Algorithm Illustration

The algorithm is formulated with 4 stages, which are briefly described below: (i) in the start, the stage of data pre-processing is define, in this stage the reading of the data, creation of the spectrum and spectrogram image are performed; (ii) after, features are extracted using feature descriptors based on images, spectrum and audio signal; (iii) after that, the stage of analysis of the features is defined to analyze and identify their discrimination capacity to categorize events in the acoustic landscape; to achieve this objective, various visual and numerical approaches would be employed that assisted in the evaluation and determination of the most discriminant features; (iv) finally the stage of visualization of the instances by multidimensional projections, allows the user to visually evaluate the quality of the features reflected in the visual separability between the categories of events. Further details are presented in the Algorithm (1).

Algorithm 1 Algorithm to identify discriminant features.

Input:

data: labeled set of sound files from an acoustic landscape.

 $model_embedded$: Extra Trees Classifier (ETC) model to determine the importance of the features.

 $model_learn$: Random Forest Classifier RFC, Support Vector Classifier SVC, k-nearest neighbors Classifier KNNC ou Extreme Gradient Boosting Classifier XBGC.

Output:

 $X_{discriminat}$: more discriminant features for a determinate acoustic landscape.

```
1: Y \leftarrow \text{Labels}(data)
                                                                                                                //sound file labels
 2: repeat = True
3: while repeat == True \ do
          // Stage (1): pre-processing data
         \hat{X} \leftarrow \text{PreprocessinData}(data)
4:
                                                                                                          //pre-processing of data
          // Stage (2): feature description
         X_{index} \leftarrow \text{IndexFeatureDescription}(X)
5:
                                                                                                         //acoustic index features
         X_{spectrum} \leftarrow \text{SpectrumFeatureDescription}(X)
 6:
                                                                                                              //spectrum features
         X_{image} \leftarrow \text{ImageFeatureDescription}(X)
                                                                                                    //spectrogram image features
 7:
         X_{raw} \leftarrow (X_{index} \cup X_{spectrum} \cup X_{image})
 8:
                                                                                                                    //total features
          // Stage (3): discriminant feature analysis
         X_{cleaned} \leftarrow \text{FeatureCleaning}(X_{raw})
                                                                                                               //cleaning features
9:
         X_{normalized} \leftarrow \text{FeatureNormalization}(X_{cleaned})
10:
                                                                                                      //normalization of features
         X_{analyzed} \leftarrow \text{FeatureAnalysis}(X_{normalized})
11:
                                                                                                            //analysis of features
         X_{important} \leftarrow \text{FeatureSelection}(model\_embedded, X_{analyzed})
12:
                                                                                                         //importance of features
         X_{ranking} \leftarrow \text{FeatureRanking}(X_{important})
13:
                                                                                                             //ranking of features
         X_{discriminant} \leftarrow [\emptyset]
                                                                                     //to store the more discriminant features
14:
         max \quad acc \leftarrow 0
                                                                                            //store value of maximum accuracy
15:
         for each i \in \{0, ..., |X_{ranking}|\} do
                                                                                     //for each features of acording to ranking
16:
              X \leftarrow (X^0_{ranking}, ..., X^i_{ranking})
                                                                                     //get be the first n features of the ranking
17:
              acc \leftarrow \text{Learning}(model \ learn, X, Y)
18:
                                                                             //train a model and compute test accuracy (acc)
19:
              if acc > max\_acc then
                                                                                       //compute the maximum accuracy value
                  X_{discriminant} \leftarrow X
20:
                  max\_acc \leftarrow acc
21:
             end if
22:
23:
         end for
          // Stage (4): visualization
         view \leftarrow \operatorname{Projection}(X_{discriminant})
24:
                                                                                                          //viusalization the data
         repeat \leftarrow UserVisualEvaluation(view)
25:
                                                                                              //the user evaluates the repetition
26: end while
```