

Title	Time-dependent performance of Dublin Port Tunnel
Authors	Wang, Chao;Friedman, Miles;Li, Zili
Publication date	2020-08
Original Citation	Wang, C., Friedman, M. and Li, Z. (2020) 'Time-dependent Performance of Dublin Port Tunnel', Civil Engineering Research in Ireland 2020: Conference Proceedings, Cork Institute of Technology, 27-28 August, pp. 659-664. isbn: 978-0-9573957-4-9. Available at: https://sword.cit.ie/monographs/1
Type of publication	Conference item;Book chapter
Link to publisher's version	https://sword.cit.ie/monographs/1
Download date	2025-08-28 00:39:48
Item downloaded from	https://hdl.handle.net/10468/15810



University College Cork, Ireland Coláiste na hOllscoile Corcaigh

# **Time-dependent Performance of Dublin Port Tunnel**

Chao Wang<sup>1</sup>, Miles Friedman<sup>2</sup>, Zili Li<sup>1</sup> <sup>1</sup>Civil, Structural and Environmental Engineering, University College Cork, Cork, Ireland <sup>2</sup>Transport Infrastructure Ireland, Dublin, Ireland Email: <sup>1</sup>chao.wang@ucc.ie, <sup>2</sup>miles.friedman@tii.ie, <sup>3</sup>zili.li@ucc.ie

ABSTRACT: It is widely observed that existing tunnels deform and deteriorate over time due to various factors. Among them, tunnel lining permeability plays a significant role. In practice, the development of lining cracks and adjustment of drainage system may gradually alter the permeability of tunnel lining and water drainage path around a tunnel with time. Nevertheless, past investigations usually assume unchanged lining permeability during the whole life of a tunnel but fail to take time-dependent aging process into consideration. In this study, a set of hydro-mechanical coupled analyses is conducted to evaluate the effect of time-dependent crack development on the behaviour of a cross passage twin-tunnel section in Dublin Port Tunnel. The numerical results compare the transverse and longitudinal settlement profiles above the twin-tunnel with and without cross passage. The deformational characteristics of tunnel lining subject to the influence of the time-dependent permeability change are also analysed, which brings more insights into the understanding of aging tunnel structures.

KEY WORDS: Time-dependent lining permeability; Cross passage; Tunnel performance; Hydro-mechanical coupled analysis.

# 1 INTRODUCTION

Tunnel structure inevitably deforms and deteriorates over time due to the influence of various factors, such as tunnel geometric profiles, mechanical characteristics, soil geological properties, etc. Among them, the permeability of both tunnel lining and surrounding soil is of great importance [1]: the permeability of soil governs how groundwater flows inside the soil, whilst the permeability of lining controls tunnel's hydraulic performance (e.g. water seepage) and subsequently has an impact on its mechanical and deformational responses [2].

To assess the effect of lining permeability on tunnel performance, field measurements from Gourvenec et al. [3] showed that in London Clay, permeable linings caused a reduction of pore water pressure around the tunnel whilst this reduction was barely observed around impermeable linings. Based upon numerical analyses, Wongsaroj et al. [4] noted ground heave for impermeable tunnels excavated in London Clay and continuous surface settlement for permeable ones in the long term. As a further study, Li et al. [5] evaluated the effect of lining permeability on the long-term tunnel performance around a cross-passage section in London Clay, and found that the increase of lining permeability led to the build-up of long-term consolidation settlement at the ground surface. Nevertheless, recent studies addressed the effect of ageing lining permeability on tunnel structural performance in the long term. Wu et al. [6] conducted a numerical analysis on the impact of localised groundwater leakage on ground and tunnel performance and predicted that a localised leakage at the joints of a segmented tunnel led to inclined oval-shaped tunnel deformation. Likewise, Shin et al. [7] pointed out that the hydraulic deterioration of joints (i.e. the blockage of segment joints) of a segmented tunnel resulted in changes in the bending moment, hoop thrust and deformation of the segments. Li et al. [8] reported that due to the influence of a temperature-related lining permeability deterioration on a seasonal basis, the widening and shrinkage of the ring joint opening of an aged segmented tunnel repeated annually.

Many of the previous studies primarily assumed the permeability of tunnel linings to be constant throughout the whole life of tunnels. In practice, however, tunnel lining permeability gradually changes over time due to structural and hydraulic deterioration. Moreover, the hydraulic deterioration mentioned in many past investigations [7, 9, 10] mainly considered the degradation as a result of drainage system blockage (deduction of permeability coefficient) rather than the increase of lining permeability due to factors such as concrete crack development which forms water leakage channels. Furthermore, limited research has been conducted to investigate the ground and tunnel behaviour around cross passage sections which, theoretically, are more structurally critical, compared with other non-cross passage sections.

In this study, a set of hydro-mechanical coupled numerical analyses was conducted to evaluate the effect of timedependent permeability increase caused by lining crack development on the long-term performance of a twin-tunnel cross passage section in Dublin Port Tunnel (DPT). The influence of cross passage and tunnel lining permeability on surface settlement was examined, and the numerical results on tunnel deformational performance were evaluated against onsite observations.

# 2 PROJECT BACKGROUND

As a project built to channel heavy goods vehicles travelling between Dublin Port and Dublin City, DPT has been in operation for more than a decade since its opening in 2006. According to historical inspection and maintenance records, it was found that the twin-tunnel structures have developed some deformation and deterioration, such as lining cracks, water

seepage, concrete spalling, etc., of which water leakage and lining cracks have been two serious issues for engineering maintenance. Along the whole tunnel alignment, the sections with obvious water seepage and concrete cracks were found around four enlarged layby sections joined by vehicle cross passages (VCP). However, the degree of tunnel deformation and deterioration around these four sections varies, with the most serious lining cracks and water ingress concentrating around VCP16 which was located at the lowest elevation along the alignment, as illustrated in Figure 1 (red dot). Based on maintenance records and previous site visits, the deterioration around this section has been developing for several years after construction with no evidence of stabilisation, which may pose a challenge to tunnel serviceability in the long run. Besides, some later-added drainage ditches were also found around layby tunnel circumference at VCP16 to flow water into the main drainage pump buried underneath the tunnel invert. The two types of degradation practically influence the water flow regime around tunnels, indicating the change of water boundary conditions or lining permeability. The linings around section VCP16 are composed of both primary and secondary linings, with the details listed as follows: (1) VCP: 200mm shotcrete primary lining and 500mm in-situ concrete secondary lining; (2) layby tunnel: 200mm shotcrete primary lining and 500mm insitu concrete secondary lining; (3) bored tunnel: 115mm nominal annular grout, 350mm concrete segmental lining and 275mm nominal in-situ concrete inner lining.



Figure 1. Location of target tunnel section [11]

# 3 FINITE ELEMENT SIMULATION

# 3.1 Ground condition and model profile

Dublin Port Tunnel, mainly consisting of northern and southern cut-and-cover sections, in-between bored section, and surface road, goes through different geological stratigraphy along its alignment [12]. Of particular interest in this study is VCP16 section in bored section buried 19.5m beneath ground surface where the most severe structural and hydraulic deterioration occurs, including lining cracks, tunnel leakage, concrete spalling, etc. The target section features a twin layby tunnel in irregular oval shape, with a spacing of around 40m, transversely connected by a horseshoe-shaped VCP for emergency evacuation and longitudinally linked by a headwall structure to the circular bored tunnel with an outer diameter of 11.77m, as shown in Figure 2.



Figure 2. Numerical model of DPT

Considering symmetrical tunnel configuration in both transverse and longitudinal directions, a quarter finite element model of the twin-tunnel cross passage was developed. To minimise boundary effect, the dimension of the model is 100m (length)  $\times$ 100m (width)  $\times$ 80m (depth), which is as much as eight times greater than the tunnel diameter. Vertical displacement at bottom of the model was fixed while the top was free. The back and right boundaries were allowed moving vertically but not moving perpendicularly to boundary faces, whereas the front and left sides were assumed as symmetrical planes.

According to DPT geotechnical investigation report [13] and previous studies [14], the general geological profile along the depth at this section is given as follows: (1) sandy clayey gravel (SCG) (0-4.8m); (2) sandy gravelly clay (SGC) (4.8-8.3m); (3) argillaceous calcisilitie (AC) (i.e. limestone) (8.3-80.0m). The physical and mechanical parameters, such as permeability, elastic modulus, cohesion, etc., are listed in Table 1. The initial pore water pressure was considered as hydrostatic with the groundwater table at 2.0m below ground surface.

The model was discretised by finite element analysis software ABAQUS [15] using 4-node linear coupled displacement-pore pressure tetrahedron element (C3D4P), with finer mesh at and around tunnel structures and coarser mesh at the further boundaries as to minimise computational cost without compromising accuracy [8]. The tunnel linings were all modelled using 3D continuous solid elements, which are the same as soil units. No interface was considered as the tunnel

Material	$\gamma$ (kN/m <sup>3</sup> )	е	<i>k</i> (m/s)	E (MPa)	v	C (kPa)	φ (°)	$K_0$
SCG	20.00	0.400	6.40×10 <sup>-8</sup>	60.0	0.30	47.8	30.0	0.50
SGC	22.00	0.300	4.80×10 <sup>-6</sup>	100.0	0.30	120.0	35.0	0.50
AC	26.64	0.233	6.10×10 <sup>-8</sup>	38.2	0.15	30.0	48.0	1.00
LC	25.00	/	/	30.0	0.30	/	/	/

Table 1. Soil and concrete properties

Note:  $\gamma$  is the dry density, *e* is the void ratio, *k* is the permeability coefficient, *E* is the elastic modulus, *v* is the Poisson's ratio, *C* is the cohesion,  $\varphi$  is the internal angle of friction and  $K_0$  is the horizontal earth pressure coefficient at rest.

lining is very unlikely to slip away from the surrounding ground during soil consolidation [8]. The whole 3D model was comprised of 465,529 elements and 75,723 nodes. A Mohr-Coulomb constitutive model was adopted for all soils and a linear elastic model was assigned to concrete. The physical and mechanical properties of lining concrete are given in Table 1.

# 3.2 Tunnel construction and long-term consolidation

On the basis of construction history, the excavation of VCP followed shortly after the construction of main tunnels (MT, i.e. bored tunnel, headwall and layby tunnel). In general, there are four main stages in this numerical modelling: initial geostatic equilibrium state, MT construction, VCP construction and long-term consolidation, as detailed in Table 2.

Table 2. General stages considered in FE analyses

Stages	Stage description					
1	1. Initial geostatic equilibrium state					
2	2.1. Excavation of MT and MT nodal force					
	reduction to 50%					
	2.2. Activation of MT linings and further MT					
	nodal force reduction to 0%					
3	3.1. Excavation of VCP and VCP nodal force					
	reduction to 50%					
	3.2. Activation of VCP linings and further VCP					
	nodal force reduction to 0%					
4	4. Long-term soil consolidation					

After initial geostatic equilibrium state, the soil elements of MT were removed first, followed by the application of nodal force around MT external circumference. To simulate the stress redistribution after MT excavation and the time lag before the installation of tunnel linings, the equivalent nodal forces were relaxed to 50% of its original magnitude, with subsequent placement of linings and another nodal force reduction of 50%. The same process was also adopted for VCP excavation before long-term consolidation begins.

# 3.3 Lining permeability change with time

After tunnel construction, the presence of lining structures may create different types of new drainage boundaries within the soil mass depending on the permeability difference between soil and lining. During ground consolidation with time, two basic scenarios may occur:

(1) The blockage of water drainage system around tunnel lining potentially caused by limestone concretion due to calcite precipitation on tunnel drainage paths [10];

(2) The cracking/construction joints-induced water seepage or infiltration into tunnels which may lead to the change of tunnel lining permeability [1].

To model these two time-dependent effects on tunnel performance, the clogged drainage system was simulated by decreasing the coefficient of tunnel lining permeability whilst cracking-induced water leakage was considered by the increase of lining permeability [1]. Due to limited space, only crackinginduced water infiltration modelled by increasing lining permeability was considered in this study. The details of cases considered in this study are listed in Table 3. As DPT has been in operation for over 14 years, the lining permeability was assumed to change linearly during this period.

Table 3.	Cracking-	induced	lining	permeability	change
rable 5.	Cracking	maacca	mmg	permeability	change

Cases	$k_l$ at the start of the 14-year period	$k_l$ at the end of the 14-year period
A1	2.0×10 <sup>-10</sup> m/s	2.0×10 <sup>-9</sup> m/s
A2	2.0×10 <sup>-10</sup> m/s	$0.5 \times 10^{-8}  \text{m/s}$
A3	$2.0 \times 10^{-10} \text{ m/s}$	$2.0 \times 10^{-8}  \text{m/s}$
A4	$2.0 \times 10^{-10} \mathrm{m/s}$	$0.5 \times 10^{-7} \mathrm{m/s}$
A5	$2.0 \times 10^{-10} \mathrm{m/s}$	2.0×10 <sup>-7</sup> m/s
A6	$2.0 \times 10^{-10} \mathrm{m/s}$	2.0×10 <sup>-6</sup> m/s

# 4 RESULTS AND DISCUSSION

# 4.1 Ground response

#### Transverse consolidation settlement

Previous efforts have investigated the long-term hydraulicmechanical coupled performance of tunnels with different relative permeability between tunnel lining and surrounding soil layers [1, 4, 16]. In this section, the effect of cross passage on long-term ground settlement above twin tunnels is specifically examined subject to different relative groundlining permeability.



Figure 3. Transverse consolidation settlement in the long term

Figure 3 shows the effect of lining permeability on the longterm surface consolidation settlement in the transverse direction for twin-tunnels with and without cross passage. For both types of twin tunnels, the maximum consolidation settlement in the long term occurs at the centreline of VCP16, indicating that the existence of VCP has no impact on the location of maximum surface settlement in the long term. The lower the tunnel lining permeability is, the smaller ground surface subsidence would be. When the tunnel lining is relatively impermeable compared with the surrounding soil (e.g. lining permeability  $k_l = 2.0 \times 10^{-9}$  m/s < soil permeability  $k_s=6.1\times10^{-8}$  m/s), the existence of cross passage leads to smaller consolidation settlement above the twin tunnel with cross passage than that for one without cross passage. This is due to the buoyancy effect of watertight tunnel with the increasing water pressure around the tunnel during ground consolidation [8]. However, the difference of maximum consolidation settlement for twin tunnels with and without cross passage becomes less significant for higher lining permeability cases,

from 0.32mm for impermeable lining  $(k_l=2.0\times10^{-9}\text{m/s})$  to approximately 0.0mm for permeable lining  $(k_l=2.0\times10^{-6}\text{m/s})$ . The findings show agreement with the conclusion by Li et al. [8] that for permeable cast-iron twin tunnels excavated in lower-permeability stiff London Clay, the effect of cross passage on the long-term surface ground settlement is negligible. That is, the soil consolidation due to drainage into cross passage barely changes the drainage characteristics around fully permeable twin tunnels.

#### Longitudinal consolidation settlement

Figure 4 shows how the existence of cross passage affects the long-term consolidation settlement of surface ground above cross passage along the longitudinal direction for tunnels with different permeability change. When tunnel lining is relatively impermeable, the existence of cross passage in twin tunnels leads to smaller longitudinal settlement than that for one without cross passage, as noted in the transverse consolidation settlement. When the tunnel becomes more permeable (i.e.  $k_l \ge$  $0.5 \times 10^{-7}$  m/s), the cross-passage effect becomes negligible. This is because the lining permeability of a twin-tunnel without cross passage is sufficiently high to enable the complete dissipation of negative excess pore water pressure generated during tunnel construction, while the contribution from cross passage drainage barely changes the water flow regime. Generally, the effect of cross passage on longitudinal consolidation settlement in the long term may not be significant from the engineering assessment point of view. Along the longitudinal direction, it can be seen that generally, the surface settlement almost remains constant at further sections from cross passage, and even, the maximum settlement is less than 2.5mm for fully permeable linings. The deflection ratio DR which is usually adopted to assess the risk of potential damage to surface structures caused by tunnelling activities is defined in equation (1) [17]:

$$DR = \Delta/L \tag{1}$$

where  $\Delta$  is the relative vertical deflection and *L* is the length of sagging zone.

It can be calculated that the DR of 0.02‰ in this case is far smaller than the recommended threshold 0.67% at which



Figure 4. Longitudinal surface settlement in the long-term

structural damage may occur [18]. This indicates that the permeability change of tunnel linings in this analysis, big or small, barely can cause any damage to ground buildings or structures.

# 4.2 Tunnel deformation

#### Tunnel deformation at cross passage opening

Figure 5(*a*) shows the change of vertical diameter with time for layby tunnel along the cross-passage section. For tunnels with a permeability increase from  $2.0 \times 10^{-10}$  m/s to  $2.0 \times 10^{-9}$  m/s, the tunnel lining deforms linearly during the 14-year period with no sign of stabilisation, which is in line with continuous development of deformation observed in DPT. This is because the negative pore water pressure generated during tunnel construction has not fully dissipated by the end of this period, indicating that the consolidation process may continue before a steady-state flow condition within surrounding soil is reached. As the degree of permeability increase becomes higher, tunnel vertical deformation builds up faster. The time it needs to reach stabilisation lessens while the magnitude of final vertical



(a). Layby tunnel vertical deformation at CP opening



(*b*). Layby tunnel horizontal deformation at CP opening Figure 5. Tunnel deformation at CP opening

diameter change increases. When the tunnel lining permeability degrades from  $2.0 \times 10^{-10}$  m/s to  $2.0 \times 10^{-6}$ m/s, the development of tunnel vertical deformation stabilises shortly after tunnel completion (approximately 300 days). This can be attributed to the accelerating dissipation of negative pore water pressure induced by the significant permeability increase, thus leading to rapid tunnel deformation. The results show that during the 14 years, a gradual increase of lining permeability causes gradual build-up of tunnel deformation while a substantial increase leads to rapid development and stabilisation

Similarly, as shown in Fig 5(*b*), the pattern of tunnel horizontal deformation is consistent with that of vertical deformation. The less permeable tunnel lining is (e.g.  $k_l \le 2.0 \times 10^{-8}$  m/s), the slower tunnel horizontal deformation is in the long term. The increase of lining permeability contributes to fast development of horizontal diameter change. When tunnel linings become fully permeable (e.g.  $k_l \ge 0.5 \times 10^{-7}$  m/s), the horizontal deformation reaches stabilisation within less than 1000 days. The reason for this is the same as that for vertical diameter change.

# Tunnel deformation at further sections

Due to limited space in this paper, the tunnel deformation at father sections is presented for case A3 with a permeability change from  $2.0 \times 10^{-10}$  m/s to  $2.0 \times 10^{-8}$  m/s only.







Figure 6(a) illustrates the development of layby tunnel deformation at four different sections (i.e. 0m, 8m, 12m and 16m away from cross passage) over time in both horizontal and vertical directions. In general, the tunnel deformation profile of gradual development at further sections remains consistent with that at cross passage section, with the maximum vertical and horizontal deformation at 0.20mm and 0.06mm, respectively. The change of horizontal diameter at the incomplete cross passage section is smaller than that of further sections because only right spring-line point is recorded at that section. The results indicate that the layby tunnel exhibits a consistent deformation mode of squatting along the traffic direction, as represented in Figure 6(b). Besides, most of the layby tunnel squatting experiences a gradual build-up during the 14-year period and predictably it may take some more time for tunnel deformation to stabilise. As for other cases listed in Table 3, it can be forecasted that the tunnel deformation at further sections follows that significant increase of lining permeability leads to faster stabilisation of tunnel squatting whilst slight increase means a relatively longer period of deformation before it can level off.

# 4.3 Effect of cross passage and time-dependent hydraulic deterioration

In general, the effect of cross passage on the long-term surface settlement is dependent on relative permeability between tunnel lining and adjacent soil. Table 4 summarises the settlement difference caused by soil consolidation for tunnels with and without cross passage in the long. If the tunnel lining is relatively impermeable, compared to surrounding soil stratum (e.g. case A1), the existence of cross passage reduces surface settlement and leads to a settlement difference of 0.32 in the long term. With the tunnel lining becoming more permeable (e.g. case A6), the effect becomes negligible.

Table 4. Difference of long-term surface settlement (mm)

Cases	A1	A2	A3	A4	A5	A6
Transverse	0.32	0.18	0.04	0.02	0.02	0.02
Longitudinal	0.32	0.18	0.04	0.02	0.02	0.02

The time-dependent increase of lining permeability reflects the realistic tunnel deformational performance. If the tunnel deteriorates slightly, a gradual development of tunnel deformation is observed, indicating the time-dependent development of tunnel structural defects. However, for tunnels that degrade significantly, the tunnel deformation shows a substantial build-up shortly after tunnel completion and then stabilises within a short period of time.

# 5 CONCLUSION

This paper conducted numerical analyses on the effect of cross passage and time-dependent hydraulic deterioration on ground response and tunnel performance in the long term. The main conclusions derived from the results are as follows:

1. For the permeable lining, the presence of cross passage may create a new drainage channel between twin tunnels. The additional cross passage drainage, however, is unable to substantially alter the surrounding water pressure, which has already dissipated into the permeable twin tunnels. Hence, the presence of cross passage makes little change on the long-term surface settlement of permeable twin tunnels in both transverse and longitudinal directions.

- 2. If the lining is impermeable, the twin tunnel with a cross passage leads to smaller consolidation settlement than that without a cross passage, due to buoyancy effect by water pressure below the watertight cross passage.
- 3. The less permeable the tunnel is, the slower tunnel deformation development is in the long term. If tunnel permeability increases gradually with time (e.g. from  $2.0 \times 10^{-10}$  m/s to  $2.0 \times 10^{-9}$  m/s), the tunnel deformation also builds up gradually, generally in line with observed continuous tunnel deformation years after construction. If tunnel permeability increases substantially at a significantly fast rate (e.g. from  $2.0 \times 10^{-10}$  m/s to  $2.0 \times 10^{-6}$  m/s), the tunnel deformation builds up rapidly and then stabilises within a short period of time.
- 4. After 14 years of soil consolidation, the layby tunnel shows a general squatting deformation mode along the longitudinal direction, regardless of the distance away from cross passage.

In this study, only time-dependent hydraulic tunnel deterioration was considered and the permeability of lining was assumed to increase linearly with time. In practice, however, hydraulic deterioration may not follow a linear relationship, whilst tunnel mechanical degradation (e.g. lining stiffness reduction) also develop with time. Further studies can be performed to examine such time-dependent effects on ground response and tunnel behaviour

## ACKNOWLEDGEMENTS

This work is jointly-funded by Science Foundation Ireland and Transport Infrastructure Ireland. The financial support is greatly appreciated. The authors want to thank Jeff Burt from Transport Infrastructure Ireland and Shane Little from Egis Road and Tunnel Operation for their kind help and support for this project.

#### REFERENCES

- Shin, J. H., S., Kim, S. H, and Shin, Y. S. (2012), 'Long-term mechanical and hydraulic interaction and leakage evaluation of segmented tunnels', *Soils and Foundations*, 52, No. 1, 38-48.
- [2] Shin, J. H., Addenbrooke, T. I. and Potts, D. M. (2002), 'A numerical study of the effect of groundwater movement on long-term tunnel behaviour'. *Géotechnique*, 52, No. 6, 391-403
- [3] Gourvenec, S. M., Mair, R. J., Bolton, M. D. and Soga, K. (2005). 'Ground conditions around an old tunnel in London Clay', Proceedings of Institution of Civil Engineers: Geotechnical Engineering, 158, 25-33.
- [4] Wongsaroj, J., Soga, K. and Mair, R. J. (2013). 'Tunnelling-induced consolidation settlement in London Clay', *Géotechnique*, 63, No. 13, 1103-1115.
- [5] Li, Z., Soga, K. and Wright, P. (2015). 'Long-term performance of castiron tunnel cross passage in London Clay', *Tunnelling and Underground Space Technology*, 50, 152-170.
- [6] Wu, H. N., Shen, S. L., Chen, R. P. and Zhou, A. (2020). 'Threedimensional numerical modelling on localised leakage in segmental lining of shield tunnels', *Computers and Geotechnics*, in press, 2020.
- [7] Shin, J. H., Kim, S. H. and Shin, Y. S. (2012). 'Long-term mechanical and hydraulic interaction and leakage evaluation of segmented tunnels', *Soils and Foundations*, 52 (1), 38-48.
- [8] Li, W., Afshani, A., Akagi, H. and Oka, S. (2020). 'Influence of lining permeability and temperature on long-term behaviour of segmented tunnel', *Soils and Foundations*, in press, 2020.
- [9] Shin, J. H., Potts, D. M. and Zdravkovic, L. (2005). 'The effect of porewater pressure on NATM tunnel linings in decomposed granite soil', *Canadian Geotechnical Journal*, 42, 1585-1599.

- [10] Mrro, V. D. (2019). 'Long-term performance of a concrete-lined tunnel at CERN', PhD thesis, University of Cambridge, UK.
- [11] Skpper, J., Follett, B., Menkiti, C. O., Long, M. and Clark-Hughes, J. (2005). 'he engineering geology and characterisation of Dublin Boulder Clay', *Qarterly Journal of Engineering Geology and Hydrogeology*, 38 (2), 171187.
- [12] MCabe, B. A., Orr, T. L. L, Reilly, C. C. and Curran, B. G. (2012). 'Settlemnt trough parameters for tunnels in Irish glacial tills', *Tunnelling and Underground Space Technology*, 27, 1-12.
- [13] GC Consult-Arup Joint Venture. (1999). Dublin Port Tunnel Site Investigation Data Reports, Dublin, Ireland.
- [14] Long, M. and Menkiti, C. O. (2007). 'Geotechnical properties of Dublin Boulder Clay', *Géotechnique*, 57, No. 7, 595-611.
- [15] Dassault Syste`mes Simulia Corp. (2019). 'Abaqus user's manual, version 2019', Providence, R.I., USA
- [16] Zhang, D. M., Ma, L. X., Zhang, J., Hicher, P. Y. and Juang, C. H. (2015). 'Ground and tunnel responses induced by partial leakage in saturated clay with anisotropic permeability', *Engineering Geology*, 189, 104-115.
- [17] Franzius, J. N., Potts, D. M. and Burland, J. B. (2006). 'The response of surface structures to tunnel construction', *Proceedings of the Institution* of Civil Engineers: Geotechnical Engineering, 159, 3-17.
- [18] Burland, J. B. (1995). 'Assessment of risk and damage to buildings due to tunnelling and excavation', Imperial College of Science, Technology and Medicine, London, UK.