




Title	Effects of pre-treatment and biological acidification on fermentative hydrogen and methane co-production
Authors	Sun, Chihe;Xia, Ao;Fu, Qian;Huang, Yun;Lin, Richen;Murphy, Jerry D.
Publication date	2019-02-19
Original Citation	Sun, C., Xia, A., Fu, Q., Huang, Y., Lin, R. and Murphy, J. D. (2019) 'Effects of pre-treatment and biological acidification on fermentative hydrogen and methane co-production', Energy Conversion and Management, 185, pp. 431-441. doi:10.1016/j.enconman.2019.01.118
Type of publication	Article (peer-reviewed)
Link to publisher's version	<a href="http://www.sciencedirect.com/science/article/pii/S0196890419301943">http://www.sciencedirect.com/science/article/pii/S0196890419301943</a> - 10.1016/j.enconman.2019.01.118
Rights	© 2019, Elsevier Ltd. All rights reserved. This manuscript version is made available under the CC BY-NC-ND 4.0 license. - <a href="https://creativecommons.org/licenses/by-nc-nd/4.0/">https://creativecommons.org/licenses/by-nc-nd/4.0/</a>
Download date	2024-04-25 06:21:02
Item downloaded from	<a href="https://hdl.handle.net/10468/7546">https://hdl.handle.net/10468/7546</a>



## Highlights

- Synergistic effects of pre-treatment and bio-acidification were assessed.
- Hydrothermal acid pre-treatment was beneficial for biological acidification.
- Increasing bio-acidification time increased acetic acid production.
- Bio-acidification decreased lag-phase time whilst improving methane production.
- 144 hours bio-acidification achieved maximum energy conversion efficiency of 64%.

1     **Effects of pre-treatment and biological acidification on fermentative**  
2     **hydrogen and methane co-production**

3     Chihe Sun <sup>a, b</sup>, Ao Xia <sup>\*, a, b</sup>, Qian Fu <sup>a, b</sup>, Yun Huang <sup>a, b</sup>, Richen Lin <sup>c, d</sup> and Jerry D.  
4     Murphy <sup>c, d</sup>

5

6     <sup>a</sup> *Key Laboratory of Low-grade Energy Utilization Technologies and Systems, Chongqing*  
7     *University, Ministry of Education, Chongqing 400044, China*

8     <sup>b</sup> *Institute of Engineering Thermophysics, College of Energy and Power Engineering, Chongqing*  
9     *University, Chongqing 400044, China*

10    <sup>c</sup> *MaREI Centre, Environmental Research Institute, University College Cork, Cork, Ireland*

11    <sup>d</sup> *School of Engineering, University College Cork, Cork, Ireland*

12

13    <sup>\*</sup> Corresponding authors:

14    Emails: aoxia@cqu.edu.cn (Ao Xia).

15    Tel./fax: +86 23 65102474.

## Abstract

A sequential two-stage process comprising biological acidification followed by anaerobic digestion was proposed to enhance gaseous biofuel production from the mixture of rice residue and microalgae with thermo-chemical hydrolysis. The maximum specific hydrogen yield of  $223.1 \pm 8.8$  mL/g volatile solids (VS) and production rate of  $10.4 \pm 0.4$  mL/g VS/h were achieved from hydrothermal acid pre-treated biomass during biological acidification. Increase in hydraulic retention time of biological acidification from 12 to 144 hours significantly affected the distribution of solubilised metabolic products and led to improve biological acidification rates (BARs) from 15.5% to 78.5%. Compared with single stage anaerobic digestion, the first stage acidification phase led to reductions in the lag-phase time and peak time of anaerobic digestion in such a two-stage process. The maximum specific methane production rate of  $2.2 \pm 0.03$  mL/g VS/h was achieved with a deep acidification of 144 hours yielding a BAR of 78.5%. Increasing the length of time in biological acidification from 12 to 144 hours contributed to improve energy conversion efficiency of 25.4%–64% after 120 hours of anaerobic digestion. These results demonstrate that biological acidification is feasible to improve bioenergy recovery in two-stage fermentation.

**Keyword:** Fermentation; Hydraulic retention time; Biological acidification; Biomethane; Algae; Food waste.

# 1    **1    Introduction**

2    Biofuels, such as biogas, biodiesel and bioethanol, are alternative renewable options  
3    for carbon intensive transport fossil fuels; they can significantly reduce greenhouse  
4    gas emissions, improve air quality and increase the security of energy supply [1-4].  
5    Compared with liquid biofuels, gaseous biofuels (such as biogas) generally have more  
6    advantages [5-7], especially in the energy conversion efficiency, greenhouse gas  
7    emissions, and the convenience of distribution system. Biogas can be used as an  
8    energy source for various applications including heat, electricity, and vehicle fuel [8].  
9    Additionally, biogas can substitute for all natural gas applications when injected to the  
10   gas grid [2].

11        Anaerobic digestion is a well-established bioconversion technology, in which  
12   various types of biomass and organic wastes can be converted to biogas by anaerobic  
13   microorganisms at relatively low temperature (35–55 °C) and ambient pressure [9,10].  
14   This technology comprises four stages (hydrolysis, acidogenesis, acetogenesis, and  
15   methanogenesis) all of which require interaction between different types of  
16   microorganisms [6,11]. However, the microorganisms in each stage have different  
17   metabolic pathways and activities, and can be disturbed by environmental stresses and  
18   undesirable process factors (such as pH, temperature, and retention time). As such, the  
19   environment and the process variables need to be optimised to ensure a high  
20   efficiency for biogas production in anaerobic digestion.

21        Previous studies found that the growth rate of acidogens at the acidogenesis stage  
22   was far superior than that of methanogens at the methanogenesis stage, especially

1 when easily degradable feedstock (such as food waste) was used as fermentation  
2 substrate [12]. Based on this, the production capacity of volatile fatty acids (VFAs) by  
3 acidogens would exceed the ability of methanogens to process the VFAs [12].  
4 Excessive accumulation of VFAs can cause a significant drop of pH, thereby  
5 hindering the fermentative methane production [13]. A separate process of biological  
6 acidification prior to anaerobic digestion is considered as one of the effective methods  
7 to avoid this imbalance between VFA production and methanogenic consumption.  
8 And not only that, hydrogen produced via biological acidification would become  
9 another key renewable energy product. The addition of hydrogen to methane can  
10 overcome several disadvantages of pure methane in engines, such as high ignition  
11 temperature, slow burning speed and narrow flammability range [6].

12 Notably, the biochemical conversion efficiency and biological stability in such a  
13 two-stage process are affected by the biological acidification rate (BAR) of feedstocks  
14 [14,15]. This can be controlled by adapting the hydraulic retention time (HRT) of  
15 biological acidification. A short HRT generally results in a low BAR with a low VFA  
16 production rate, corresponding to a low hydrogen yield [6,16]. Also, the insufficient  
17 substrates of VFAs for methanogens in anaerobic digestion would further lead to a  
18 low methane yield. A long HRT favours the complete degradation of feedstocks and  
19 produces a high concentration of VFA. Even so, the composition and concentration of  
20 soluble metabolic products (SMPs), such as alcohols and VFAs, differ with different  
21 HRTs [17]. The performance of the subsequent methane producing stage is influenced  
22 by these SMPs. For instances, the bioactivity of methanogens is inhibited at a

propionic acid concentration of 900 mg/L, while the inhibitory concentrations of ethanol, acetic acid, and butyric acid were higher than 1800 mg/L [18].

Additionally, the biological acidification process is also closely related to the physicochemical properties of feedstocks and the intensities of pre-treatment [19-22].

For easily degradable biomass, a relatively low HRT is sufficient for acidogens to achieve the high hydrolysis and acidification efficiencies, subsequently resulting in significant increases in hydrogen and methane yields [6]. However, to ensure an effective biological acidification of recalcitrant feedstocks, the HRT has to be sufficiently high [6]. Since the release and hydrolysis of high-molecular intracellular organic matters for recalcitrant feedstocks can be enhanced by the application of pre-treatment, this technology is generally used to decrease the HRT of biological acidification and improve the subsequent fermentation performance [19-22]. It should be noted that the side reactions, such as the self-decomposition of sugars (or amino acids) and Maillard reactions between sugars and amino acids, would also occur during thermo-chemical pre-treatment of biomass, especially for mixtures of carbohydrate-rich and protein-rich biomass [23]. Some of toxic by-products produced from these adverse reactions, such as furans and phenols, may inhibit the bioactivity of enzymes and damage the structures of DNA, further impeding the fermentation pathway during biological acidification and subsequent anaerobic digestion [24,25].

Overall, the gap in the state of the art is the study of synergistic effects of pre-treatment and biological acidification at various HRTs on anaerobic digestion, especially for the substrates with significantly different physicochemical properties. In



this study, the easily degradable rice residue (RR) with high content of carbohydrates and the slowly degradable microalgae *Chlorella pyrenoidosa* (CP) with high content of proteins were hydrothermally pre-treated, and then the mixture was used as the co-fermentation feedstock. The objectives of the present study are to:

- Analyse the impacts of various HRTs on biological acidification.
- Evaluate the synergistic effects of pre-treatment and biological acidification on subsequent anaerobic digestion.
- Assess the bioenergy recovery characteristics of gaseous biofuel production from co-fermentation of algae and rice residues.

## 2 Materials and methods

### 2.1. Substrates and inocula

RR was collected from a dining hall in Chongqing University, China. To remove the attached greases, the RR was washed thoroughly using deionized water. Subsequently, the treated RR was blended into pulp using a blender. RR pulp was loaded into zip-lock bags and then stored at  $-20\text{ }^{\circ}\text{C}$  before use. CP powder was purchased from Yantai Hairong Biotechnology Co., Ltd., China. The purchased CP powder was stored at room temperature in a dry environment before use. The characteristics of RR pulp and CP powder are shown in Table 1.

The inocula for biological acidification were collected from a rural domestic biogas digester in China. The raw sludge was heated at  $100\text{ }^{\circ}\text{C}$  for 30 min in an autoclave (Boxun YXQ-LS-SII, China). After heating treatment, the acidogens survived through forming spores, while the methanogens were deactivated. To revive

1 and enrich the acidogens, the heat-treated sludge was acclimatized 3 times (72 hours  
2 for each time interval) using a modified culture medium at 35 °C under an anaerobic  
3 environment [26]. Total solids (TS) and volatile solids (VS) of the activated acidogens  
4 were 116.9 and 73.1 g/kg fresh weight, respectively. The inocula for anaerobic  
5 digestion were collected from the same biogas digester. The raw sludge was filtered  
6 by a 2-mm sieve to remove large particles, and subsequently acclimatized 3 times  
7 (168 hours for each time interval) using cellulose (1.5 g/L) at 35 °C under an  
8 anaerobic environment. TS and VS of the activated methanogens were 58.2 and 27.1  
9 g/kg fresh weight, respectively.

## 10 2.2. *Pre-treatment of mixed biomass*

11 The hydrothermal (140 °C, 10 min) and hydrothermal acid pre-treatment (140 °C, 10  
12 min, 1% (v/v) H<sub>2</sub>SO<sub>4</sub>) were carried out in triplicate in a 70 mL reaction kettle  
13 (Taikang QN-WCGF, China) [27]. The working volume of this reaction kettle was 50  
14 mL. The mixed raw RR and CP (2.5 g TS) were pre-treated at a VS ratio of RR to CP  
15 of 25 [27], corresponding to a C/N molar ratio of 31.3. After hydrothermal acid  
16 pre-treatment, the pH values of biomass hydrolysates were adjusted to  $7.5 \pm 0.1$  using  
17 3 M NaOH and HCl solutions. The hydrolysates composed of solubilised matters  
18 together with solid residues were loaded into 50 mL centrifuge tubes and then stored  
19 at -20 °C before being used as fermentation substrates. Mixed RR and CP without  
20 pre-treatment was set as the control group.

## 21 2.3. *Biological acidification*

22 The experimental design details of biological acidification and subsequent anaerobic

1 digestion as well as direct anaerobic digestion are shown in Fig 1. Biological  
2 acidification was performed in triplicate in 500 mL glass fermenters with an effective  
3 working volume of 300 mL each. The mixed RR and CP hydrolysates including  
4 solubilised matters and solid residues (containing 5 g TS) were used in biological  
5 acidification. A certain amount of deionized water was added to each fermenter to  
6 maintain an overall volume of 270 mL, and then the fermenters were inoculated with  
7 30 mL of activated acidogens. The initial pH values were adjusted to  $6.5 \pm 0.1$  using 3  
8 M NaOH and HCl solutions [28,29]. All the fermenters were sealed with rubber  
9 stoppers, and nitrogen was purged for 5 min to ensure an anaerobic environment. The  
10 biological acidification process was operated in a thermostatic water bath at  $35.0 \pm$   
11  $0.5$  °C under various HRTs (12–144 hours). During biological acidification, the pH  
12 values were adjusted to  $6.5 \pm 0.1$  using 3 M NaOH and HCl solutions at  
13 predetermined time intervals (6 or 12 hours). The produced gases were released from  
14 the headspace of fermenters, collected in graduated gas collectors [30], and then  
15 recorded at each predetermined time interval [27]. A blank group only containing  
16 inocula and a control group using raw mixed biomass with no pre-treatment as  
17 substrate were also operated under the same experimental procedure.

#### 18 *2.4. Anaerobic digestion*

19 Anaerobic digestion was performed in triplicate in the AMPTS II system (Bioprocess  
20 Control, Sweden) [31]. The biological acidification effluents (BAEs) including  
21 supernatants and solid residues were transferred to 500 mL glass fermenters and then  
22 used as substrate in anaerobic digestion. Each fermenter with a working volume of

1 410 mL contained 150 mL of BAEs and 260 mL of methanogens, corresponding to a  
2 substrate to inoculum VS ratio of 1:2 [32,33]. The initial pH values were adjusted to  
3  $7.5 \pm 0.1$  using 3 M NaOH and HCl solutions. All the fermenters were sealed with  
4 rubber stoppers, purged with nitrogen for 5 min, and then placed in a water bath at  
5  $35.0 \pm 0.5$  °C for 720 hours. During anaerobic digestion, the pH values were without  
6 control. A blank group only containing inocula and a control group (direct anaerobic  
7 digestion) separately using raw, hydrothermal pre-treated, and hydrothermal acid  
8 pre-treated mixed biomass, and cellulose as substrate were also operated under the  
9 same experimental procedure.

10 Notably, the AMPTS II system cannot analyse the composition of the produced  
11 gases. To measure the yields of hydrogen and methane produced during the initial 72  
12 hours of anaerobic digestion, the produced gases contained hydrogen, methane, and  
13 carbon dioxide were firstly collected in the graduated gas collectors and then recorded  
14 at every 12 hours, as previously discussed. Differently, this process had no pH  
15 adjustment. After the initial 72 hours of anaerobic digestion, the produced gases  
16 would contain only methane and carbon dioxide. The fermentation reactors could be  
17 connected to the carbon dioxide adsorption unit in the AMPTS II system and then  
18 the yield of methane could be automatically recorded and measured by a build-in  
19 tipping device [31].

## 20 2.5. Analytical methods

21 The carbohydrates, reducing sugars, proteins, lipids, TS, and VS were measured as  
22 described in the previous studies [34,35]. A spectrophotometer (Hach DR3900, USA)

1 coupled with a heating digestion unit (Hach DRB200, USA) was used to analyse the  
2 chemical oxygen demand (COD) and total ammonia nitrogen (TAN) [27]. An  
3 elemental analyser (Elementar Vario MACRO cube, Germany) was applied to  
4 measure the C, H, N, and S contents [36]; the remaining VS content was determined  
5 as O [36,37]. The pH values were measured by a portable pH meter (METTLER F2,  
6 Switzerland). Hydrogen, methane, and carbon dioxide were determined by a gas  
7 chromatograph (GC) (Thermo Trace 1300, USA) equipped with a micro-packed  
8 column (ShinCarbon ST Columns, 2 m, OD 1/16, ID 1.0 mm, Mesh 100/120) and a  
9 thermal conductivity detector (TCD) [25,36]. The contents of SMPs including ethanol,  
10 acetic acid, propionic acid, butyric acid, valeric acid, and caproic acid were analysed  
11 using another GC (Agilent 7890B, USA) equipped with a polar capillary column  
12 (Agilent DB-FFAP Column, 30 m  $\times$  0.25 mm  $\times$  0.25  $\mu$ m) and a flame ionization  
13 detector (FID) [36,38]. All experimental trials and measurements were conducted in  
14 triplicate, and the results were expressed as the average  $\pm$  standard deviation.

## 15 2.6. Calculations

16 The BAR (%) was calculated using the ratio of the total COD weight of SMPs to the  
17 total COD weight of initial mixed biomass. The specific hydrogen yield (SHY) and  
18 methane yield (SMY) (mL/g VS) were calculated based on the volume of total gases  
19 (normalized to zero moisture content, standard temperature of 0 °C and pressure of 1  
20 atm) and content of hydrogen and methane both in the gas collector and fermenter  
21 headspace at each time interval [27]. Thereafter, the SHY and SMY were simulated  
22 using a modified Gompertz equation [39]; the kinetic parameters including the

maximum production potential ( $H_m$ , mL/g VS), peak rate ( $R_m$ , mL/g VS/h), peak time ( $T_m$ , h), and lag-phase time ( $\lambda$ , h) were calculated through the Origin software.

The higher heating values of hydrogen and methane were determined as 286 and 889 kJ/mol, respectively [29,36]. The higher heating values (kJ/g VS) of RR and CP were calculated using the Mendeleev formula, Eq. (1). Where, C, H, O, and S represent the VS percentage of each element in the initial biomass, respectively. Additionally, the energy recovery characteristics were quantitatively analysed by energy conversion efficiency (ECE) and energy conversion percentage (ECP<sub>120</sub>). The ECE (%) and ECP<sub>120</sub> (%) were calculated based on the Eqs. (2) – (3).

$$\text{Heating value (kJ/g VS)} = 0.33858C + 1.254H - 0.10868(O - S) \quad (1)$$

$$\text{ECE (\%)} = \frac{\text{Total energy value (kJ) of the produced hydrogen and methane}}{\text{Total energy value (kJ) of initial mixed biomass}} \times 100 \quad (2)$$

$$\text{ECP}_{120} (\%) = \frac{\text{ECE (\%)} \text{ based on 120 hours of anaerobic digestion}}{\text{Total ECE (\%)} \text{ based on the complete anaerobic digestion}} \times 100 \quad (3)$$

### 3 Results and Discussion

#### 3.1. Comparison of organic matter solubilisation from different pre-treatments

The effects of hydrothermal and hydrothermal acid pre-treatment were analysed in terms of solubilised COD, carbohydrates, proteins, and reducing sugars, as shown in Fig. 2. The initial concentration of solubilised carbohydrates and proteins derived from raw biomass were only  $4.27 \pm 0.18$  and  $0.43 \pm 0.02$  g/L, respectively, corresponding to  $6.63 \pm 0.76$  g solubilised COD/L. Meanwhile, the low reducing sugar concentration of  $0.86 \pm 0.01$  g/L indicated that most of solubilised carbohydrates presented in the form of starch, which is the main polysaccharide in RR and CP [40].

After hydrothermal pre-treatment, carbohydrates ( $28.77 \pm 0.89$  g/L) and proteins ( $1.87 \pm 0.32$  g/L) in the soluble phase increased 5.7-fold and 3.3-fold, respectively. This illustrated that RR and CP cells could be effectively disrupted by hydrothermal pre-treatment. Nevertheless, the reducing sugar concentration ( $1.87 \pm 0.24$  g/L) only constituted 6.5% of solubilised carbohydrates. The hydrolysis of starch into reducing sugars such as maltose and glucose is due to the fracture of glycosidic bonds. Without adding any chemicals, the glycosidic bonds of starch are more difficult to damage under a relatively low reaction time (10 min) and temperature (140 °C) [27].

When raw biomass was subjected to hydrothermal acid pre-treatment, the reducing sugar concentration ( $45.53 \pm 3.3$  g/L) significantly increased 52.2-fold and 23.3-fold, respectively, compared with raw and hydrothermal pre-treated biomass. Unexpectedly, this concentration was more than the total concentration of solubilised carbohydrates ( $42.06 \pm 2.6$  g/L). Previous studies found that monosaccharides such as galactose and glucose could further break down into various by-products under severe pre-treatment conditions in the presence of acids [41-43]; some of these by-products may present reduction properties, which caused the high detected reducing sugar concentration [27]. Additionally, monosaccharide can react with amino acids, which is named as the Maillard reaction [44,45]. The Maillard products may also possess the reducing groups such as free aldehyde and ketone groups [27]. Thus, excess reducing sugars detected in the hydrolysates could be caused by the formation of these reducing substances.

### *3.2. Effects of different pre-treatments on biological acidification*

### 3.2.1 Degradation of organic matters

The degradation effects of solubilised organic matters before and after biological acidification are shown in Table 2. When hydrothermal and hydrothermal acid pre-treated biomass were separately fermented for 144 hours, the concentrations of solubilised carbohydrates were significantly decreased from 9.59–14.02 g/L to 0.32–0.47 g/L. Whereas, the changes in the concentrations of solubilised proteins (from 0.62–1.92 g/L to 0.4–0.56 g/L) were not obvious. This indicated that carbohydrates were more readily utilised by acidogens than proteins. Previous studies found that amino acids derived from proteolysis were not suitable substrates for hydrogen production during biological acidification; the negligible SHYs were generally ranged from 0.2 to 16.2 mL/g VS [46,47]. Therefore, hydrogen could be mainly produced from the fermentation of carbohydrates. Additionally, the low final concentration of solubilised carbohydrates from raw biomass (0.16 g/L) indicated that organics in the solid substance would be also hydrolysed and utilized by acidogens.

### 3.2.2 Biohydrogen production

Fig. 3 depicts the effects of pre-treatment methods on fermentative hydrogen production during biological acidification. When raw RR and CP were used as mixed substrate, the maximum SHY and specific hydrogen production rate (SHPR) were only  $100.7 \pm 6.6$  mL/g VS and  $2.7 \pm 0.3$  mL/g VS/h, respectively. Since the organic matters in the raw biomass were tightly surrounded by the intact biomass cell wall, the low concentrations of solubilised carbohydrates ( $1.42 \pm 0.07$  g/L) and proteins ( $0.14 \pm 0.00$  g/L) were insufficient to maintain the bioactivity and growth of acidogens [36],



as shown in Table 2. Additionally, high-molecular polysaccharides were difficultly to hydrolyse and utilise by acidogens [48]. A low reducing sugar concentration ( $0.29 \pm 0.01$  g/L) before biological acidification resulted in low SHY and SHPR.

When hydrothermal pre-treated biomass was used as substrate, the maximum SHY and SHPR increased to  $169.5 \pm 25.0$  mL/g VS and  $5.8 \pm 0.4$  mL/g VS/h, respectively. This could be attributed to the improvements in the damage to the biomass structures and the release of intracellular carbohydrates ( $9.59 \pm 0.28$  g/L) and proteins ( $0.62 \pm 0.09$  g/L). However, the low hydrolysis efficiency of polysaccharides during hydrothermal pre-treatment also resulted in low reducing sugar concentration ( $0.62 \pm 0.11$  g/L), which still resulted in an unsatisfactory level of hydrogen production during biological acidification.

When hydrothermal acid pre-treatment was applied to hydrolyse raw biomass, the maximum SHY and SHPR significantly increased to  $223.1 \pm 8.8$  mL/g VS and  $10.4 \pm 0.4$  mL/g VS/h respectively, which shows 2.2-fold and 3.8-fold increases compared with the values obtained from raw biomass. This was due to the highest concentrations of solubilised organic matters especially reducing sugars ( $15.18 \pm 0.23$  g/L) before biological acidification. Meanwhile, the increase of available carbon and nitrogen sources effectively promoted the biomass degradation by acidogens [49,50].

The kinetic parameters of fermentative hydrogen production derived from the modified Gompertz model are presented in Table 3. The highest SHY potential of  $223.7$  mL/g VS and SHPR of  $10.8$  mL/g VS/h were obtained from hydrothermal acid pre-treated biomass. Compared with raw biomass without/with hydrothermal

1 pre-treatment, the high amounts of easily degradable low-molecular organic matters  
2 obtained from hydrothermal acid pre-treatment also effectively shortened the  
3 lag-phase time (decreased from 6.7 to 4.2 hours) and peak time (decreased from 21.9  
4 to 11.8 hours) of biological acidification.

### 5 *3.2.3 Production of soluble metabolite products*

6 As shown in Table 2, the SMPs in the effluents of biological acidification contained  
7 abundant butyric acid (6.18–9.51 g COD/L) and acetic acid (2.62–3.86 g COD/L), and  
8 a small quantity of propionic acid (0.27–1.54 g COD/L), caproic acid (0.99–1.11 g  
9 COD/L), ethanol (0.22–0.39 g COD/L) and valeric acid (0.12–0.2 g COD/L). In this  
10 case, acidogens mainly conducted acetic acid and butyric acid pathways. The total  
11 SMP concentration obtained from raw, hydrothermal pre-treated, and hydrothermal  
12 acid pre-treated biomass were  $11.75 \pm 0.35$ ,  $13.16 \pm 0.58$  and  $15.19 \pm 0.14$  g COD/L,  
13 respectively, corresponding to the BARs of  $60.7 \pm 1.2\%$ ,  $68.0 \pm 2.0\%$  and  $78.5 \pm 1.2\%$ .  
14 Compared with hydrothermal and hydrothermal acid pre-treatment, the concentration  
15 of propionic acid ( $1.54 \pm 0.01$  g COD/L) from raw biomass without pre-treatment was  
16 1.2-fold and 4.7-fold higher, respectively. Since the production of propionic acid is  
17 considered as an unfavourable hydrogen consuming pathway [51], such a  
18 phenomenon may be another explanation for the relatively lower SHY and SHPR  
19 obtained from raw biomass.

20 The concentrations of TAN derived from amino acid hydrolysis increased to the  
21 range of 40.3–204.8 mg/L. But such a concentration is still below the suggested  
22 threshold level (4000 mg/L) that negatively affects the bioactivity of acidogens [13].

This further confirmed that co-fermentation of RR and CP could effectively mitigate the inhibitory effects of TAN accumulation during biological acidification.

### *3.3. Effects of hydraulic retention time on biological acidification*

The hydrothermal acid pre-treated biomass was used as fermentation substrate to assess the effects of various HRTs on biological acidification. As shown in Fig. 3 and Table 2, when the HRT was set as 12 hours, the final concentration of solubilised carbohydrates and proteins were still as high as  $9.5 \pm 1.53$  and  $0.88 \pm 0.09$  g/L, which are  $67.8 \pm 3.5\%$  and  $45.8 \pm 2.1\%$  of the initial concentration, respectively. Meanwhile, a low BAR of  $15.5 \pm 0.6\%$  and a low SHY of  $87.2 \pm 0.8$  mL/g VS were obtained from converting biomass to SMPs ( $3.0 \pm 0.34$  g COD/L). Rathbun et al. and Xia et al. found that acidogens required a few hours lag-time (3–6 hours) to develop the ability to degrade specific organic matters [52,53]. Such a short HRT of 12 hours in biological acidification was insufficient for complete biomass degradation, as well as high SMP and hydrogen production.

When the HRT was increased to 48 hours, the concentration of solubilised carbohydrates significantly decreased from 9.5 to 1.04 g/L, thereby leading to a high SHY of  $222.4 \pm 8.9$  mL/g VS, a high SMP production of  $14.47 \pm 0.13$  g COD/L and a high BAR of  $74.7 \pm 1.4\%$ . However, the change in the concentration of solubilised proteins was not obvious (from 0.88 to 0.62 g/L). During the adaptation period (0–12 hours), a certain amount of proteins (1.04 g/L) were hydrolysed and then used as the nitrogen sources to sustain the growth and reproduction of acidogens. After the bioactivity of acidogens was effectively improved (12–48 hours), monosaccharide

1 consumption by acidogens generally preceded amino acid consumption [46], as  
2 previously discussed. The conservative increases of TAN concentration ranged from  
3  $13.5 \pm 1.1$  to  $42.7 \pm 3.0$  mg/L confirmed such an explanation.

4 The non-obvious decrease trend for the concentration of solubilised proteins  
5 (from 0.62 to 0.6 g/L) was not disappeared when the HRT was increased to 72 hours.  
6 Differently, since monosaccharide was largely exhausted, the utilisation of amino  
7 acids derived from proteolysis was greatly enhanced, resulting in an obvious increase  
8 in TAN ( $120.1 \pm 6.9$  mg/L). Even so, due to the low-effective fermentative hydrogen  
9 production of amino acids [46,47], the SHY ( $222.4 \pm 8.9$  mL/g VS), the SMP  
10 production ( $15.03 \pm 0.32$  g COD/L), and the BAR ( $77.6 \pm 0.8\%$ ) were similar to these  
11 obtained after 48 hours fermentation. This also indicated that hydrogen production via  
12 biological acidification had been completed during the period of 48–72 hours.

13 When a long HRT of 144 hours was applied to acidize biomass, the final TAN  
14 concentration further increased to  $204.8 \pm 11.6$  mg/L. Although a relative in-depth  
15 acidification has no significant effects on improving the SHY ( $223.1 \pm 8.8$  mL/g VS),  
16 the SMP production ( $15.19 \pm 0.14$  g COD/L), and the BAR ( $78.5 \pm 1.2\%$ ), the  
17 distribution of SMPs was altered. To be specific, at the end of rapid biological  
18 acidification period (about 24 hours), the concentrations of propionic acid, valeric  
19 acid, and caproic acid were only  $0.05 \pm 0.01$ ,  $0.01 \pm 0.00$ , and  $0.11 \pm 0.01$  g COD/L,  
20 respectively. However, after biological acidification of 144 hours, their final  
21 cumulative concentrations increased to  $0.27 \pm 0.01$ ,  $0.12 \pm 0.00$ , and  $1.08 \pm 0.04$  g  
22 COD/L, respectively. Hydrogen could be consumed during the production of these

three types of VFAs [6,54]. This may be one reason for the non-obvious increases in SHY. Some hydrogen and carbon dioxide could be also converted to acetic acid via the homoacetogenic pathway, thereby resulting in the increase in acetic acid concentration ( $3.86 \pm 0.19$  g COD/L). Additionally, the decrease in butyric acid concentration ( $9.51 \pm 0.19$  g COD/L) also suggested that a long HRT of biological acidification may lead to a mutual transformation of different SMPs.

Noblecourt et al. reported that the process of hydrogen production via biological acidification would obviously decrease when the mass concentration of VFAs exceeded 12.5 g/L [55]. In this study, the COD concentration of VFAs obtained from 12–144 hours fermentation were in the range of 2.74–14.85 g COD/L (Table 2), corresponding to the mass concentration of 1.78–9.58 g/L. These values are much lower than the threshold level. Besides, the pH values for biological acidification were all adjusted to  $6.5 \pm 0.1$  at each predetermined time interval (6 or 12 hours). Therefore, the inhibitory effects caused by the pH drop and VFA accumulation would be fully mitigated during the whole period of biological acidification.

### *3.4. Methane production during anaerobic digestion*

#### *3.4.1 Direct anaerobic digestion*

When cellulose was used as substrate for direct anaerobic digestion, the maximum SMY was  $311.5 \pm 2.2$  mL/g VS. This result suggested a healthy inoculum condition, and the bioactivity of methanogens for converting cellulose to methane was already within the acceptable range [31]. Fig. 4a shows the SMYs obtained from raw, hydrothermal pre-treated, and hydrothermal acid pre-treated biomass during direct

1 anaerobic digestion. Based on raw biomass, the maximum SMY of  $220.0 \pm 0.2$  mL/g  
2 VS was relatively low due to the presence of unbroken biomass cell structures. After  
3 hydrothermal pre-treatment, the maximum SMY increased to  $272.4 \pm 0.8$  mL/g VS,  
4 indicating that the application of pre-treatment could also improve the performance of  
5 anaerobic digestion [56]. Whereas, a severe pre-treatment such as the use of dilute  
6 acid led to an obvious decrease in SMY ( $255.7 \pm 1.2$  mL/g), which was a totally  
7 different trend to hydrogen production during biological acidification. This was  
8 attributed to the combined action of anaerobic mixed microflora and special  
9 fermentation substrate.

10 The anaerobic mixed microflora used in methane production contained various  
11 types of microorganism such as acidogens and methanogens. Since starch could be  
12 effectively hydrolysed into reducing sugars under hydrothermal acid pre-treatment,  
13 the easily degradable substrates especially RR (more than 90% of starch) were rapidly  
14 degraded by acidogens, resulting in the accumulation of VFAs and decrease of pH  
15 ( $5.03 \pm 0.51$ ) at the early stage of direct anaerobic digestion (0–48 hours). Thus, the  
16 growth of methanogens would be inhibited [6], thereby achieving a relatively low  
17 SMY.

18 In fact, such negative effects also occurred during direct anaerobic digestion  
19 from raw and hydrothermal pre-treated biomass, which was directly reflected through  
20 the fluctuation of specific methane production rates (SMPRs), as shown in Fig. 4b. On  
21 the first 24 hours of direct anaerobic digestion, the SMPRs were as high as 1.5–2.0  
22 mL/g VS/h, suggesting efficient substrate degradation and methane production. Su et

al. reported that acidogens generally grew faster than methanogens [12]. As previously discussed, the VFAs produced by acidogens were more than the VFAs consumed by methanogens. The excessive accumulation of VFAs resulted in a significant drop of pH and a rapid decrease of SMPRs (only 0.01–0.12 mL/g VS/h) in the next 72 hours. After an adaptation period of 216–312 hours, the accumulated VFAs were gradually consumed, and the SMPRs climbed back to 1.9–2.2 mL/g VS/h with the recovery of methanogens.

In direct anaerobic digestion, the produced hydrogen in the acidogenesis process could not be completely consumed by methanogens at the initial stage of fermentation (0–72 hours). As a result, a significant amount of hydrogen was generated from raw, hydrothermal pre-treated, and hydrothermal acid pre-treated mixed biomass with maximum SHYs of  $56.1 \pm 2.3$ ,  $106.4 \pm 4.1$ , and  $141.1 \pm 5.6$  mL/g VS, respectively.

As shown in Table 3, the fitting coefficients from fermentative methane production via direct anaerobic digestion using the modified Gompertz equation were in the range of 0.9379 to 0.9797, which are lower than the values from anaerobic digestion with biological acidification. The unstable methane production caused by the accumulation of VFAs generated a big difference between the kinetic fitting parameters and the experimental data.

#### *3.4.2 Effects of pre-treatments on anaerobic digestion after biological acidification*

Fig. 5 shows the effects of pre-treatments on anaerobic digestion after biological acidification. The BAEs derived from 144 hours of biological acidification with optimal adjusted pH values of around 7.5 were used as substrate in the subsequent

1 anaerobic digestion process. Since most of the organic matters especially  
2 carbohydrates were degraded through biological acidification with sufficient duration,  
3 the inhibition phenomenon disappeared and no hydrogen was produced.

4 Based on the BAEs of raw mixed biomass, the maximum SMY and SMPR were  
5  $206.4 \pm 2.8$  mL/g VS and  $2.8 \pm 0.1$  mL/g VS/h, respectively. When the mixed biomass  
6 was hydrothermally pre-treated, the maximum SMY and SMPR increased to  $223.1 \pm$   
7  $0.8$  mL/g VS and  $3.2 \pm 0.1$  mL/g VS/h, respectively. This could be attributed to the  
8 fact that the BAEs of hydrothermal pre-treated biomass contained more SMPs ( $13.16$   
9  $\pm 0.58$  g COD/L) as compared with the BAEs of raw biomass ( $11.75 \pm 0.35$  g COD/L),  
10 as shown in Table 2. Generally, the performance of anaerobic digestion was positively  
11 related with the concentration of SMPs (alcohols and VFAs) in the BAEs [23]. SMPs  
12 are considered as favourable substrates for fermentative methane production.

13 Notably, when raw mixed biomass was hydrothermally pre-treated by diluted  
14 acid, the concentration of SMPs in the BAEs further increased to  $15.19 \pm 0.14$  g  
15 COD/L, while the maximum SMY and SMPR reduced to  $183.7 \pm 1.4$  mL/g VS and  
16  $2.2 \pm 0.03$  mL/g VS/h, respectively. This may be explained by the toxic by-products  
17 such as furan derivatives, phenols and the Maillard products typically derived from  
18 thermochemical pre-treatment [23]. Overall, hydrothermal pre-treatment under acid  
19 catalysis is an effective method to improve hydrogen production during biological  
20 acidification, whereas the subsequent methane fermentation of their BAEs may not  
21 perform as optimally as desired.

22 As shown in Table 3, anaerobic digestion from various BAEs (144 hours of



1 biological acidification) could be accurately described by the modified Gompertz  
2 equation with high fitting coefficients ( $R^2$  ranged from 0.9888 to 0.9926). The highest  
3 SMY potential of 224.1 mL/g VS and SMPR of 3.3 mL/g VS/h were obtained from  
4 the BAEs of hydrothermal pre-treated biomass. Compared with direct anaerobic  
5 digestion, the two-stage process comprising biological acidification and anaerobic  
6 digestion could effectively avoid inhibition caused by VFA accumulation, thereby  
7 significantly reducing the lag-phase time (decreased from 64.9–121.3 hours to  
8 21.0–23.1 hours) and peak time (decreased from 170.7–211.1 hours to 46.1–48.3  
9 hours) of anaerobic digestion. On account of this, the whole fermentation period of  
10 anaerobic digestion in two-stage process obviously decreased to 60–168 hours, around  
11 only 1/3 of direct anaerobic digestion (Figs. 4–5).

#### 12 *3.4.3 Effects of biological acidification time on anaerobic digestion*

13 The BAEs of hydrothermal acid pre-treated biomass were used as substrate to assess  
14 the effects of biological acidification time on subsequent anaerobic digestion, as  
15 shown in Fig. 6. When a short HRT of 12 hours was set for biological acidification  
16 (BAR:  $15.5 \pm 0.6\%$ ), incomplete degradation of carbohydrates (Table 2:  $9.5 \pm 1.53$   
17 g/L of residual carbohydrates) led to VFA accumulation and pH decrease at the early  
18 stage of anaerobic digestion. For this reason, the maximum SMY of  $132.3 \pm 8.7$  mL/g  
19 VS and SMPR of  $1.8 \pm 0.1$  mL/g VS/h were relatively low. Meanwhile, small  
20 amounts of hydrogen of  $40.0 \pm 2.3$  mL/g VS was observed in anaerobic digestion.

21 When the HRT of biological acidification was increased to 24 hours (BAR:  $41.0$   
22  $\pm 1.2\%$ ), most of the carbohydrates were degraded (Table 2:  $2.61 \pm 0.58$  g/L of

1 residual carbohydrates), thereby mitigating the above inhibition in anaerobic digestion.

2 Whilst, no hydrogen was produced in anaerobic digestion due to the low  
3 concentration of carbohydrates in the BAEs. Nevertheless, it was still considered as  
4 an unstable fermentative methane production process. The maximum SMY slightly  
5 increased to  $147.0 \pm 6.1$  mL/g VS, while the maximum SMPR decreased to  $1.5 \pm 0.1$   
6 mL/g VS/h.

7 When the HRT was increased to 48 hours (BAR:  $74.7 \pm 1.4\%$ ), the maximum  
8 SMY and SMPR significantly increased to  $203.1 \pm 1.0$  mL/g VS and  $2.0 \pm 0.0$  mL/g  
9 VS/h, respectively. This suggested that an appropriate improvement in biomass  
10 acidification degree could effectively enhance methane production from the BAEs.  
11 Since biological acidification had been completed during the period of 48–72 hours,  
12 further increasing the HRT of biological acidification to 72 hours (BAR:  $77.6 \pm 0.8\%$ )  
13 resulted in slight changes in the maximum SMY ( $192.0 \pm 1.8$  mL/g VS) and SMPR  
14 ( $1.9 \pm 0.1$  mL/g VS/h).

15 It should be noted that in this work a long HRT (144 hours) of biological  
16 acidification with a very small increase of BAR ( $78.5 \pm 1.2\%$ ) as compared to 72  
17 hours would lead to a lower maximum SMY of  $183.7 \pm 1.4$  mL/g VS. This  
18 unfavourable phenomenon may be caused by excessive consumption of total carbon  
19 sources during biological acidification. Some of the carbon sources may be converted  
20 to carbon dioxide and released from the fermenters, which could not be reused in  
21 subsequent anaerobic digestion. Interestingly, the maximum SMPR increased to  $2.2 \pm$   
22  $0.03$  mL/g VS/h (from  $1.9 \pm 0.1$  mL/g VS/h). This result may be attributed to the

1 increase in acetic acid concentration ( $3.86 \pm 0.19$  g COD/L), as shown in Table 2. It is  
2 known that acetic acid can be directly utilised by acetotrophic methanogens, whereas  
3 other SMPs (such as ethanol, propionic acid, and butyric acid) should be firstly  
4 degraded to acetic acid and then utilised to produce methane in methanogenesis [57].  
5 As previously discussed, a relative in-depth acidification (144 hours) could promote  
6 the further degradation of amino acids, the conversion of butyric acid to acetic acid,  
7 and the process of homoacetogenesis, thereby resulting in a high concentration of  
8 acetic acid and a high SMPR during anaerobic digestion.

9 As shown in Table 3, anaerobic digestion combined with biological acidification  
10 (with HRTs from 12 to 144 hours) also could be accurately described by the modified  
11 Gompertz equation with high fitting coefficients ( $R^2$  ranged from 0.9811 to 0.9952).  
12 The highest SMY potential of 204.1 mL/g VS was obtained after 48 hours of  
13 biological acidification. A relative in-depth biomass acidification of 144 hours showed  
14 the highest SMPR of 2.5 mL/g VS/h. These results were consistent with the  
15 experimental data. Compared with direct anaerobic digestion, different degrees of  
16 biomass acidification (15.5%–78.5%) all decreased the lag-phase time (from  
17 64.9–121.3 hours to 21.0–53.6 hours) and peak time (from 170.7–211.1 hours to  
18 48.3–81.4 hours) of anaerobic digestion in two-stage process. Furthermore, in terms  
19 of the lag-phase time and peak time, the most significant enhancement was observed  
20 after 144 hours of biological acidification with a highest BAR of  $78.5 \pm 1.2\%$ .

### 21 *3.5 Comparison of energy conversion efficiencies and energy conversion percentages*

22 The ECEs were calculated based on 120 hours of anaerobic digestion with various

1 HRT for biological acidification (0–144 hours) by using hydrothermal acid pre-treated  
2 biomass as substrate. As shown in Fig. 7(a). The ECEs from hydrogen were in the  
3 range of 10.3%–18.0%, which was still insufficiently high for industrial applications.  
4 The maximum hydrogen ECE of  $18.0 \pm 0.7\%$  was achieved after 48 hours of  
5 biological acidification with a BAR of  $74.7 \pm 1.4\%$  (Table 2). Further increasing the  
6 HRT of biological acidification had almost no effect on improving the energy  
7 conversion from hydrogen due to the non-obvious enhancement of hydrogen  
8 production (Fig. 3).

9 By combining methane production, the ECEs significantly increased to  
10 25.4%–64.0%. This growing trend was positively related to the acidification degree of  
11 biomass. For direct anaerobic digestion without biological acidification, the methane  
12 fermentation period was generally quite long (nearly 480 hours), as shown in Fig. 4.  
13 In this case, when the ECEs were calculated based on 120 hours of anaerobic  
14 digestion, the achievable maximum ECE was only  $25.4 \pm 0.3\%$  due to the low SMY  
15 of  $55.6 \pm 1.6$  mL/g VS. However, when a relative in-depth biological acidification of  
16 144 hours with a highest BAR of  $78.5 \pm 1.2\%$  (Table 2) was applied prior to anaerobic  
17 digestion, the methane production could be accomplished quickly. The maximum  
18 SMY of  $183.7 \pm 1.4$  mL/g VS (Fig. 6) had been achieved at the calculated period of  
19 anaerobic digestion of 120 hours, thereby resulting in the maximum ECE of  $64.0 \pm$   
20  $1.0\%$  from hydrogen and methane.

21 Compared with the ECEs obtained from 120 hours of anaerobic digestion  
22 (25.4%–64.0%), the total ECEs based on the complete fermentation process were in

1 the range of 43.5%–75.6%. Notably, the ratio of the two parameters was defined as  
2 the  $ECP_{120}$  (see Equation 3), which could be used to assess the effects of biological  
3 acidification on the required time to achieve the maximum total ECE. As shown in Fig.  
4 7(b), the  $ECP_{120}$  from direct anaerobic digestion was only  $33.5 \pm 0.4\%$ , indicating that  
5 raw biomass without biological acidification could not be rapidly degraded to produce  
6 methane. Once raw biomass underwent biological acidification, even only 12 hours of  
7 biological acidification with a low BAR of  $15.5 \pm 0.6\%$  (Table 2), the corresponding  
8  $ECP_{120}$  ( $84.3 \pm 0.9\%$ ) still increased 1.5-fold. However, by increasing the HRT of  
9 biological acidification to 72 hours (BAR:  $77.6 \pm 0.8\%$ ), the increase of  $ECP_{120}$   
10 slightly increased from  $84.3 \pm 0.9\%$  to  $89.6 \pm 1.2\%$ .

11 Such a phenomenon was caused by the presence of high amounts of easily  
12 degradable organic matters in the mixed biomass of RR and CP (i.e., starch). Since  
13 these substrates could be readily used by acidogens, a short-term biological  
14 acidification (12–72 hours) was sufficient to enhance subsequent methane production  
15 via anaerobic digestion. Although the BAR of  $78.5 \pm 1.2\%$  only slightly increased  
16 during a relative in-depth biological acidification of 144 hours duration, the  
17 distribution of SMPs revealed obvious differences (Table 2). As previously discussed,  
18 the high concentration of acetic acid would finally realize a rapid methane production  
19 with a maximum SMPR of  $2.2 \pm 0.03$  mL/g VS/h (Fig. 6), thereby leading to a  
20 maximum  $ECP_{120}$  of  $99.8 \pm 0.1\%$ . Overall, an in-depth biological acidification could  
21 effectively accelerate the subsequent fermentative methane production, and achieve  
22 the maximum potential of energy conversion over a short time frame corresponding to

a small volume and lower capital investment.

## **4 Conclusion**

The biological acidification rates (60.7%–78.5%) would maximally increase 1.3-fold with enhancing the intensity of biomass pre-treatment, thereby achieving the maximum specific hydrogen yield of  $223.1 \pm 8.8$  mL/g VS and production rate of  $10.4 \pm 0.4$  mL/g VS/h. Increasing the hydraulic retention time of biological acidification (12–144 hours) had significant effects on improving biological acidification rates (15.5%–78.5%). Meanwhile, such a phenomenon could further affect the performance of subsequent fermentative methane production. A relative in-depth biological acidification of 144 hours resulted in the minimum lag-phase time and peak time of anaerobic digestion. The whole anaerobic digestion period (120 hours) decreased by 70% with a maximum methane production rate of  $2.2 \pm 0.03$  mL/g VS/h. Moreover, the energy conversion efficiency based on 120 hours of anaerobic digestion combined with an in-depth biological acidification was  $64.0 \pm 1.0\%$ , which shows 2.5-fold increase compared with direct anaerobic digestion.

## **Acknowledgements**

This work is supported by the National Science Foundation for Young Scientists of China (No. 51606021), the State Key Program of National Natural Science of China (No. 51836001), the Venture & Innovation Support Program for Chongqing Overseas Returnees (No. cx2017019), and the Fundamental Research Funds for the Central Universities (Nos. 2018CDXYDL0001, 2018CDYJSY0055). Dr Richen Lin acknowledges the support from the European Commission's Marie Skłodowska-Curie

1 grant No. 797259. Prof Jerry D. Murphy is funded by Science Foundation Ireland  
2 (SFI) through the Centre for Marine and Renewable Energy (MaREI) under Grant No.  
3 12/RC/2302.  
4

## References

- [1] Tian X, Liao Q, Liu W, Wang YZ, Zhu X, Li J, et al. Photo-hydrogen production rate of a PVA-boric acid gel granule containing immobilized photosynthetic bacteria cells. *Int. J. Hydrogen Energ.* 2009;34(11):4708-17.
- [2] Tian X, Liao Q, Zhu X, Wang Y, Zhang P, Li J, et al. Characteristics of a biofilm photobioreactor as applied to photo-hydrogen production. *Bioresource Technol.* 2010;101(3):977-83.
- [3] Gebremariam SN, Marchetti JM. Economics of biodiesel production: Review. *Energ. Convers. Manage.* 2018;168:74-84.
- [4] Chang H, Quan X, Zhong N, Zhang Z, Lu C, Li G, et al. High-efficiency nutrients reclamation from landfill leachate by microalgae *Chlorella vulgaris* in membrane photobioreactor for bio-lipid production. *Bioresource Technol.* 2018;266:374-81.
- [5] Budzianowski WM, Brodacka M. Biomethane storage: Evaluation of technologies, end uses, business models, and sustainability. *Energ. Convers. Manage.* 2016;141(1):254-73.
- [6] Xia A, Cheng J, Murphy JD. Innovation in biological production and upgrading of methane and hydrogen for use as gaseous transport biofuel. *Biotechnol. Adv.* 2016;34(5):451-72.
- [7] Khan IU, Hafiz M, Othman D, Hashim H, Matsuura T, Ismail AF, et al. Biogas as a renewable energy fuel—A review of biogas upgrading, utilisation and storage. *Energ. Convers. Manage.* 2017;150:277-94.
- [8] Weiland P. Biogas production: Current state and perspectives. *Appl. Microbiol. Biot.* 2010;85(4):849-60.
- [9] Kopsahelis A, Stavropoulos K, Zafiri C, Kornaros M. Anaerobic co-digestion of End-of-Life dairy products with agroindustrial wastes in a mesophilic pilot-scale two-stage system: Assessment of system's performance. *Energ. Convers. Manage.* 2018;165:851-60.
- [10] Nguyen DD, Chang SW, Jeong SY, Jeung J, Kim S, Guo W, et al. Dry thermophilic semi-continuous anaerobic digestion of food waste: Performance evaluation, modified Gompertz model analysis, and energy balance. *Energ. Convers. Manage.* 2016;128:203-10.
- [11] Saady N. Homoacetogenesis during hydrogen production by mixed cultures dark fermentation: Unresolved challenge. *Int. J. Hydrogen Energ.* 2013;38(30):13172-91.
- [12] Su YX, Karthikeyan OP, Selvam A, Wong JWC. Effect of inoculum to substrate ratio on the hydrolysis and acidification of food waste in leach bed reactor. *Bioresource Technol.* 2012;126(6):425-30.
- [13] Chen Y, Cheng J, Creamer K. Inhibition of anaerobic digestion process: A review. *Bioresource Technol.* 2008;99(10):4044-64.
- [14] Chen X, Yuan H, Zou D, Liu Y, Zhu B, Chufo A, et al. Improving biomethane yield by controlling fermentation type of acidogenic phase in two-phase anaerobic co-digestion of food waste and rice straw. *Chem. Eng. J.* 2015;273:254-60.
- [15] Gioannis DG, Diaz LF, Muntoni A, Pisanu A. Two-phase anaerobic digestion within a solid waste/wastewater integrated management system. *Waste Manag.* 2008;28(10):1801-8.
- [16] Sialve B, Bernet N, Bernard O. Anaerobic digestion of microalgae as a necessary step to make microalgal biodiesel sustainable. *Biotechnol. Adv.* 2009;27(4):409-16.
- [17] Cheng J, Ding L, Lin R, Yue L, Liu J, Zhou J, et al. Fermentative biohydrogen and biomethane co-production from mixture of food waste and sewage sludge: Effects of physiochemical properties and mix ratios on fermentation performance. *Appl. Energ.* 2016;184:1-8.



- [18] Wang Y, Zhang Y, Wang J, Meng L. Effects of volatile fatty acid concentrations on methane yield and methanogenic bacteria. *Biomass Bioenerg.* 2009;33(5):848-53.
- [19] Bundhoo MAZ, Mohee R, Hassan MA. Effects of pre-treatment technologies on dark fermentative biohydrogen production: A review. *J. Environ. Manage.* 2015;157:20-48.
- [20] Lin R, Cheng J, Murphy JD. Unexpectedly low biohydrogen yields in co-fermentation of acid pretreated cassava residue and swine manure. *Energ. Convers. Manage.* 2017;151:553-61.
- [21] Xuan J, Li M, Xi B, Zhu C, Yang Y, Xia T, et al. Integration of fermentative biohydrogen with methanogenesis from fruit-vegetable waste using different pre-treatments. *Energ. Convers. Manage.* 2014;88:1219-27.
- [22] Arun C, Sivashanmugam P. Enhanced production of biohydrogen from dairy waste activated sludge pre-treated using multi hydrolytic garbage enzyme complex and ultrasound-optimization. *Energ. Convers. Manage.* 2018;164:277-87.
- [23] Lin R, Cheng J, Murphy JD. Inhibition of thermochemical treatment on biological hydrogen and methane co-production from algae-derived glucose/glycine. *Energ. Convers. Manage.* 2018;158:201-9.
- [24] Bundhoo MAZ, Mohee R. Inhibition of dark fermentative bio-hydrogen production: A review. *Int. J. Hydrogen Energ.* 2016;41(16):6713-33.
- [25] Lin R, Cheng J, Ding L, Song W, Zhou J, Cen K. Inhibitory effects of furan derivatives and phenolic compounds on dark hydrogen fermentation. *Bioresource Technol.* 2015;196:250-5.
- [26] Cheng J, Xia A, Song W, Su H, Zhou J, Cen K. Comparison between heterofermentation and autofermentation in hydrogen production from *Arthrospira (Spirulina) platensis* wet biomass. *Int. J. Hydrogen Energ.* 2012;37(8):6536-44.
- [27] Sun C, Xia A, Liao Q, Fu Q, Huang Y, Zhu X, et al. Improving production of volatile fatty acids and hydrogen from microalgae and rice residue: Effects of physicochemical characteristics and mix ratios. *Appl. Energ.* 2018;230:1082-92.
- [28] Zhao J, Wang D, Li X, Yang Q, Chen H, Zhong Y, et al. Free nitrous acid serving as a pretreatment method for alkaline fermentation to enhance short-chain fatty acid production from waste activated sludge. *Water Res.* 2015;78:111-20.
- [29] Xia A, Jacob A, Herrmann C, Murphy JD. Fermentative bio-hydrogen production from galactose. *Energy* 2016;96:346-54.
- [30] Walker M, Yue Z, Heaven S, Banks C. Potential errors in the quantitative evaluation of biogas production in anaerobic digestion processes. *Bioresource Technol.* 2009;100(24):6339-46.
- [31] Tabassum MR, Xia A, Murphy JD. The effect of seasonal variation on biomethane production from seaweed and on application as a gaseous transport biofuel. *Bioresource Technol.* 2016;209:213-9.
- [32] Liu X, Xu Q, Wang D, Zhao J, Wu Y, Liu Y, et al. Improved methane production from waste activated sludge by combining free ammonia with heat pretreatment: Performance, mechanisms and applications. *Bioresource Technol.* 2018;268:230-6.
- [33] Wang D, Liu X, Zeng G, Zhao J, Liu Y, Wang Q, et al. Understanding the impact of cationic polyacrylamide on anaerobic digestion of waste activated sludge. *Water Res.* 2018;130:281-90.
- [34] Xia A, Jacob A, Tabassum MR, Herrmann C, Murphy JD. Production of hydrogen, ethanol and volatile fatty acids through co-fermentation of macro- and micro-algae. *Bioresource Technol.* 2016;205:118-25.
- [35] Ding L, Cheng J, Qiao D, Yue L, Li YY, Zhou J, et al. Investigating hydrothermal pretreatment of food waste for two-stage fermentative hydrogen and methane co-production. *Bioresource Technol.* 2017;241:491-9.

- [36] Xia A, Cheng J, Ding L, Lin R, Song W, Zhou J, et al. Enhancement of energy production efficiency from mixed biomass of *Chlorella pyrenoidosa* and cassava starch through combined hydrogen fermentation and methanogenesis. *Appl. Energ.* 2014;120(120):23-30.
- [37] Ge L, Zhang Y, Wang Z, Zhou J, Cen K. Effects of microwave irradiation treatment on physicochemical characteristics of Chinese low-rank coals. *Energ. Convers. Manage.* 2013;71(71):84-91.
- [38] Xia A, Cheng J, Lin R, Lu H, Zhou J, Cen K. Comparison in dark hydrogen fermentation followed by photo hydrogen fermentation and methanogenesis between protein and carbohydrate compositions in *Nannochloropsis oceanica* biomass. *Bioresource Technol.* 2013;138(6):204-13.
- [39] Lay JJ, Lee YJ, Noike T. Feasibility of biological hydrogen production from organic fraction of municipal solid waste. *Water Res.* 1999;33(11):2579-86.
- [40] Brown MR, Jeffrey SW, Volkman JK, Dunstan GA. Nutritional properties of microalgae for mariculture. *Aquacult* 1997;151(1-4):315-31.
- [41] Girisuta B, Janssen LPBM, Heeres HJ. Green chemicals: A kinetic study on the conversion of glucose to levulinic acid. *Chem. Eng. Res. Des.* 2006;84(5):339-49.
- [42] Li H, Govind KS, Kotni R, Shunmugavel S, Riisager A, Yang S, et al. Direct catalytic transformation of carbohydrates into 5-ethoxymethylfurfural with acid-base bifunctional hybrid nanospheres. *Energ. Convers. Manage.* 2014;88:1245-51.
- [43] Nur Aainaa SR, Nor Aishah SA. Optimization of renewable levulinic acid production from glucose conversion catalyzed by Fe/HY zeolite catalyst in aqueous medium. *Energ. Convers. Manage.* 2015;95:10-9.
- [44] Mendez L, Mahdy A, Timmers RA, Ballesteros M, Gonzálezfernández C. Enhancing methane production of *Chlorella vulgaris* via thermochemical pretreatments. *Bioresource Technol.* 2013;149(4):136-41.
- [45] Su JF, Zhen H, Yuan XY, Wang XY, Min L. Structure and properties of carboxymethyl cellulose/soy protein isolate blend edible films crosslinked by Maillard reactions. *Carbohydr. Polym.* 2010;79(1):145-53.
- [46] Xia A, Cheng J, Ding LK, Lin RC, Song WL, Su HB, et al. Substrate consumption and hydrogen production via co-fermentation of monomers derived from carbohydrates and proteins in biomass wastes. *Appl. Energ.* 2015;139:9-16.
- [47] Cheng J, Ding L, Ao X, Lin R, Li Y, Zhou J, et al. Hydrogen production using amino acids obtained by protein degradation in waste biomass by combined dark- and photo-fermentation. *Bioresource Technol.* 2015;179:13-9.
- [48] Su H, Cheng J, Zhou J, Song W, Cen K. Improving hydrogen production from cassava starch by combination of dark and photo fermentation. *Int. J. Hydrogen Energ.* 2009;34(4):1780-6.
- [49] Su H, Cheng J, Zhou J, Song W, Cen K. Combination of dark- and photo-fermentation to enhance hydrogen production and energy conversion efficiency. *Int. J. Hydrogen Energ.* 2009;34(21):8846-53.
- [50] Sambusiti C, Bellucci M, Zabaniotou A, Beneduce L, Monlau F. Algae as promising feedstocks for fermentative biohydrogen production according to a biorefinery approach: A comprehensive review. *Renew. Sust. Energ. Rev.* 2015;44(44):20-36.
- [51] Ghimire A, Valentino S, Frunzo L, Trably E, Escudie R, Pirozzi F, et al. Biohydrogen production from food waste by coupling semi-continuous dark-photofermentation and residue post-treatment to anaerobic digestion: A synergy for energy recovery. *Int. J. Hydrogen Energ.* 2015;40(46):16045-55.
- [52] Rathbun RE. Transport, behavior, and fate of volatile organic compounds in streams. *Crit. Rev.*

- Env. Sci. Technol. 2000;30(2):129-295.
- [53] Xia A, Cheng J, Ding L, Lin R, Huang R, Zhou J, et al. Improvement of the energy conversion efficiency of *Chlorella pyrenoidosa* biomass by a three-stage process comprising dark fermentation, photofermentation, and methanogenesis. *Bioresource Technol.* 2013;146:436-43.
- [54] Toledo-Alarcón J, Capson-Tojo G, Marone A, Paillet F, Chatellard L, Bernet N, et al. Basics of bio-hydrogen production by dark Fermentation. In *Bioreactors for microbial biomass and energy conversion*. Springer, Singapore; 2018, p. 199-220.
- [55] Noblecourt A, Christophe G, Larroche C, Santa-Catalina G, Trably E, Fontanille P. High hydrogen production rate in a submerged membrane anaerobic bioreactor. *Int. J. Hydrogen Energ.* 2017;42(39):24656-66.
- [56] Fu SF, Chen KQ, Zhu R, Sun WX, Zou H, Guo RB. Improved anaerobic digestion performance of *Miscanthus floridulus* by different pretreatment methods and preliminary economic analysis. *Energ. Convers. Manage.* 2018;159:121-8.
- [57] Zabranska J, Pokorna D. Bioconversion of carbon dioxide to methane using hydrogen and hydrogenotrophic methanogens. *Biotechnol. Adv.* 2017;36(3):707-20.
- [58] Xu Q, Liu X, Fu Y, Li Y, Wang D, Wang Q, et al. Feasibility of enhancing short-chain fatty acids production from waste activated sludge after free ammonia pretreatment: Role and significance of rhamnolipid. *Bioresource Technol.* 2018;267:141-8.
- [59] Nualsri C, Kongjan P, Reungsang A. Direct integration of CSTR-UASB reactors for two-stage hydrogen and methane production from sugarcane syrup. *Int. J. Hydrogen Energ.* 2016;41(40):17884-95.

## **List of tables and figures:**

**Table 1** Characteristics of rice residue pulp and *Chlorella pyrenoidosa* powder.

**Table 2** Degradation of organic matters and production of soluble metabolic products during biological acidification.

**Table 3** Kinetic parameters of hydrogen production during biological acidification and methane production during anaerobic digestion.

**Fig 1** Design of experiment including for anaerobic digestion combined with biological acidification and direct anaerobic digestion.

**Fig. 2** Organic matter solubilisation under different pre-treatments.

**Fig. 3** Effects of different pre-treatments on hydrogen production during biological acidification: (a) Specific hydrogen yield; (b) Specific hydrogen production rate.

**Fig. 4** Methane production during direct anaerobic digestion from raw, hydrothermal pre-treated, and hydrothermal acid pre-treated mixed biomass: (a) Specific methane yield; (b) Specific methane production rate.

**Fig. 5** Methane production during anaerobic digestion from biological acidification effluents: (a) Specific methane yield; (b) Specific methane production rate. Hydraulic retention time of biological acidification was set as 144 hours.

**Fig. 6** Effects of biomass acidification time on anaerobic digestion: (a) Specific methane yield; (b) Specific methane production rate. Substrate used in anaerobic digestion was the biological acidification effluents of hydrothermal acid pre-treated mixed biomass.

**Fig. 7** Energy conversion efficiencies and energy conversion percentages during hydrogen and methane co-production: (a) Energy conversion efficiencies; (b) Energy conversion percentages. Substrate used in anaerobic digestion was the biological acidification effluents of hydrothermal acid pre-treated mixed biomass.

**Table 1** Characteristics of rice residue pulp and *Chlorella pyrenoidosa* powder.

Parameters	Rice residue pulp	<i>Chlorella pyrenoidosa</i> powder
Proximate analysis		
Moisture (wt%)	81.84 ± 0.01	6.26 ± 0.24
TS (wt%)	18.16 ± 0.01	93.74 ± 0.24
VS (wt%)	18.03 ± 0.01	78.91 ± 0.34
VS/TS (%)	99.28 ± 0.02	84.18 ± 0.37
Ultimate analysis		
C (VS%)	43.07 ± 0.21	50.62 ± 0.17
H (VS%)	5.09 ± 0.09	6.23 ± 0.31
O (VS%)	50.04 ± 0.42	33.42 ± 0.15
N (VS%)	1.31 ± 0.01	9.31 ± 0.07
S (VS%)	0.49 ± 0.03	1.28 ± 0.04
C/N molar ratio	38.4 ± 0.13	6.35 ± 0.05
Energy value (kJ/g VS)	15.58 ± 0.52	21.46 ± 0.37
tCOD (mg/g VS)	1167.91 ± 56.33	1429.44 ± 47.18
tCarbohydrates (mg/g VS)	917.21 ± 45.57	332.98 ± 26.23
tProteins (mg/g VS)	128.12 ± 17.86	504.04 ± 32.14
tLipids (mg/g VS)	12.69 ± 2.78	169.41 ± 14.69
sCOD (mg/g VS)	118.65 ± 5.64	152.65 ± 12.74
sCarbohydrates (mg/g VS)	87.53 ± 13.65	64.62 ± 11.54
sProteins (mg/g VS)	6.65 ± 1.01	40.75 ± 0.97
Reducing sugars (mg/g VS)	14.41 ± 0.76	3.68 ± 0.24
TAN (mg/g VS)	/	1.07 ± 0.04

The abbreviation referred to total (t) and solubilised (s) matters;

TS: Total solids; VS: Volatile solids; COD: Chemical oxygen demand;

TAN: Total ammonia nitrogen;

**Table 2** Degradation of organic matters and production of soluble metabolic products during biological acidification.

Description	Pre-treatment methods						
	Without	Hydrothermal	Hydrothermal acid				
Acidification time (hours)	144	144	12	24	48	72	144
sCarbohydrate (g/L) <sup>a</sup>	1.42 ± 0.07	9.59 ± 0.28	14.02 ± 0.13	14.02 ± 0.13	14.02 ± 0.13	14.02 ± 0.13	14.02 ± 0.13
sCarbohydrate (g/L) <sup>b</sup>	0.16 ± 0.02	0.32 ± 0.01	9.5 ± 1.53	2.61 ± 0.58	1.04 ± 0.22	0.55 ± 0.09	0.47 ± 0.11
sProtein (g/L) <sup>a</sup>	0.14 ± 0.00	0.62 ± 0.09	1.92 ± 0.09	1.92 ± 0.09	1.92 ± 0.09	1.92 ± 0.09	1.92 ± 0.09
sProtein (g/L) <sup>b</sup>	0.12 ± 0.02	0.40 ± 0.13	0.88 ± 0.09	0.72 ± 0.24	0.62 ± 0.18	0.6 ± 0.11	0.56 ± 0.05
Reducing sugar (g/L) <sup>a</sup>	0.29 ± 0.01	0.62 ± 0.11	15.18 ± 0.23	15.18 ± 0.23	15.18 ± 0.23	15.18 ± 0.23	15.18 ± 0.23
Reducing sugar (g/L) <sup>b</sup>	0.04 ± 0.00	0.03 ± 0.01	8.68 ± 1.33	2.43 ± 0.21	1.01 ± 0.03	0.64 ± 0.01	0.04 ± 0.00
TAN (mg/L) <sup>b</sup>	40.32 ± 2.35	122.8 ± 8.56	13.5 ± 1.05	27.8 ± 2.31	42.7 ± 3.02	120.1 ± 6.93	204.8 ± 11.64
Total SMPs (g COD/L) <sup>c</sup>	11.75 ± 0.35	13.16 ± 0.58	3.0 ± 0.34	7.94 ± 0.32	14.47 ± 0.13	15.03 ± 0.32	15.19 ± 0.14
Ethanol (g COD/L)	0.22 ± 0.03	0.39 ± 0.05	0.26 ± 0.01	0.28 ± 0.03	0.3 ± 0.03	0.3 ± 0.03	0.34 ± 0.02
Acetic acid (g COD/L)	2.62 ± 0.15	3.39 ± 0.24	0.72 ± 0.08	1.6 ± 0.14	3.33 ± 0.21	3.49 ± 0.18	3.86 ± 0.19
Propionic acid (g COD/L)	1.54 ± 0.01	0.69 ± 0.14	0.03 ± 0.01	0.05 ± 0.01	0.09 ± 0.01	0.19 ± 0.01	0.27 ± 0.01
Butyric acid (g COD/L)	6.18 ± 0.4	7.38 ± 0.54	1.9 ± 0.16	5.88 ± 0.49	10.12 ± 0.28	10.38 ± 0.41	9.51 ± 0.19
Valeric acid (g COD/L)	0.2 ± 0.01	0.19 ± 0.01	0.01 ± 0.00	0.01 ± 0.00	0.01 ± 0.00	0.05 ± 0.01	0.12 ± 0.00
Caproic acid (g COD/L)	0.99 ± 0.07	1.11 ± 0.14	0.08 ± 0.03	0.11 ± 0.01	0.61 ± 0.03	0.62 ± 0.02	1.08 ± 0.04
BAR (%)	60.7 ± 1.23	68.0 ± 2.03	15.47 ± 0.57	40.99 ± 1.22	74.7 ± 1.35	77.64 ± 0.77	78.46 ± 1.17

TAN: Total ammonia nitrogen; SMPs: Soluble metabolic products; BAR: Biological acidification rate; COD: Chemical oxygen demand.

<sup>a</sup> Before fermentation; <sup>b</sup> After fermentation; <sup>c</sup> The concentrations of SMPs were based on the unit of “g COD/L” according to the references [58,59].


**Table 3** Kinetic parameters of hydrogen production during biological acidification and methane production during anaerobic digestion.

Processes	Substrates	Pre-treatment methods	Acidification time (hours)	Kinetic model parameters				
				$H_m$ (mL/g VS)	$R_m$ (mL/g VS/h)	$\lambda$ (h)	$T_m$ (h)	$R^2$
Biological acidification	Raw mixed	/	144	101.61	2.50	6.67	21.62	0.9952
	biomass	Hydrothermal	144	173.35	4.20	6.70	21.89	0.9876
		Hydrothermal acid	144	223.68	10.78	4.17	11.80	0.9985
Anaerobic digestion	Raw mixed	/	0	229.53	0.94	121.28	211.12	0.9379
	biomass	Hydrothermal	0	276.76	1.44	111.94	182.65	0.9797
		Hydrothermal acid	0	267.61	0.93	64.85	170.72	0.9535
	BAEs <sup>a</sup>	/	144	206.96	3.10	21.50	46.06	0.9897
	BAEs <sup>b</sup>	/	144	224.07	3.30	23.11	48.09	0.9888
	BAEs <sup>c</sup>	/	12	132.93	1.76	53.61	81.40	0.9920
		/	24	148.14	1.40	28.64	67.57	0.9811
		/	48	204.12	1.86	27.30	67.68	0.9952
		/	72	193.16	2.05	29.00	63.67	0.9897
		/	144	184.43	2.48	20.97	48.33	0.9926


BAEs: Biological acidification effluents. <sup>a</sup> BAEs of raw mixed biomass. <sup>b</sup> BAEs of hydrothermal pre-treated mixed biomass.

<sup>c</sup> BAEs of hydrothermal acid pre-treated mixed biomass.







**Fig 1** Design of experiment including for anaerobic digestion combined with biological acidification and direct anaerobic digestion.




**Fig. 2** Organic matter solubilisation under different pre-treatments.




**Fig. 3** Effects of different pre-treatments on hydrogen production during biological acidification: (a) Specific hydrogen yield; (b) Specific hydrogen production rate.




**Fig. 4** Methane production during direct anaerobic digestion from raw, hydrothermal pre-treated, and hydrothermal acid pre-treated mixed biomass: (a) Specific methane yield; (b) Specific methane production rate.



**Fig. 5** Methane production during anaerobic digestion from biological acidification effluents: (a) Specific methane yield; (b) Specific methane production rate. Hydraulic retention time of biological acidification was set as 144 hours.



**Fig. 6** Effects of biomass acidification time on anaerobic digestion: (a) Specific methane yield; (b) Specific methane production rate. Substrate used in anaerobic digestion was the biological acidification effluents of hydrothermal acid pre-treated mixed biomass.



**Fig. 7** Energy conversion efficiencies and energy conversion percentages during hydrogen and methane co-production: (a) Energy conversion efficiencies; (b) Energy conversion percentages. Substrate used in anaerobic digestion was the biological acidification effluents of hydrothermal acid pre-treated mixed biomass.