

Title	Temperature measurement of cold atoms using transient absorption of a resonant probe through an optical nanofibre
Authors	Kumar, Ravi;Gokhroo, Vandna;Tiwari, Vibhuti Bhushan;Nic Chormaic, Síle
Publication date	2016-09-29
Original Citation	Kumar, R., Gokhroo, V., Tiwari, V.B. and Nic Chormaic, S. (2016) 'Temperature measurement of cold atoms using transient absorption of a resonant probe through an optical nanofibre', Journal of Optics, 18(11), 115401 (5 pp). doi:10.1088/2040-8978/18/11/115401
Type of publication	Article (peer-reviewed)
Link to publisher's version	10.1088/2040-8978/18/11/115401
Rights	© 2016. IOP Publishing Ltd. Original content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the authors and the title of the work, journal citation and DOI https://creativecommons.org/licenses/by/3.0/
Download date	2025-06-05 04:30:15
Item downloaded from	https://hdl.handle.net/10468/3196



University College Cork, Ireland Coláiste na hOllscoile Corcaigh



Home Search Collections Journals About Contact us My IOPscience

Temperature measurement of cold atoms using transient absorption of a resonant probe through an optical nanofibre

This content has been downloaded from IOPscience. Please scroll down to see the full text. 2016 J. Opt. 18 115401 (http://iopscience.iop.org/2040-8986/18/11/115401)

View the table of contents for this issue, or go to the journal homepage for more

Download details:

IP Address: 143.239.102.76 This content was downloaded on 07/10/2016 at 12:05

Please note that terms and conditions apply.

You may also be interested in:

Optical nanofibres and neutral atoms Thomas Nieddu, Vandna Gokhroo and Síle Nic Chormaic

Sub-Doppler temperature measurements of laser-cooled atoms using optical nanofibres Laura Russell, Kieran Deasy, Mark J Daly et al.

Investigation of a 85Rb dark magneto-optical trap using an optical nanofibre Laura Russell, Ravi Kumar, Vibhuti Bhushan Tiwari et al.

Interaction of laser-cooled 87Rb atoms with higher order modes of an optical nanofibre Ravi Kumar, Vandna Gokhroo, Kieran Deasy et al.

Single atoms on an optical nanofibre K P Nayak and K Hakuta

Inhomogeneous broadening of optical transitions of 87Rb atoms in an optical nanofiber trap J Lee, J A Grover, J E Hoffman et al.

Nanostructured optical nanofibres for atom trapping M Daly, V G Truong, C F Phelan et al. **OPEN ACCESS** 

## Temperature measurement of cold atoms using transient absorption of a resonant probe through an optical nanofibre

# Ravi Kumar $^{1,2,5}$ , Vandna Gokhroo $^{1,6}$ , Vibhuti Bhushan Tiwari $^{2,3}$ and Síle Nic Chormaic $^{1,4,7}$

<sup>1</sup>Light-Matter Interactions Unit, Okinawa Institute of Science and Technology Graduate University, Onna, Okinawa 904-0495, Japan

<sup>2</sup> Physics Department, University College Cork, Cork, Ireland

<sup>3</sup> Laser Physics Applications Section, Raja Ramanna Centre for Advanced Technology, Indore 452013, India

<sup>4</sup> School of Chemistry and Physics, University of KwaZulu-Natal, Durban, KwaZulu-Natal, 4001, South Africa

E-mail: sile.nicchormaic@oist.jp

Received 17 May 2016, revised 22 August 2016 Accepted for publication 26 August 2016 Published 29 September 2016

#### Abstract

Optical nanofibres are ultrathin optical fibres with a waist diameter typically less than the wavelength of light being guided through them. Cold atoms can couple to the evanescent field of the nanofibre-guided modes and such systems are emerging as promising technologies for the development of atom-photon hybrid quantum devices. Atoms within the evanescent field region of an optical nanofibre can be probed by sending near or on-resonant light through the fibre; however, the probe light can detrimentally affect the properties of the atoms. In this paper, we report on the modification of the local temperature of laser-cooled <sup>87</sup>Rb atoms in a magneto-optical trap centred around an optical nanofibre when near-resonant probe light propagates through it. A transient absorption technique has been used to measure the temperature of the affected atoms and temperature variations from 160  $\mu$ k to 850  $\mu$ k, for a probe power ranging from 0 to 50 nW, have been observed. This effect could have implications in relation to using optical nanofibres for probing and manipulating cold or ultracold atoms.

Keywords: optical nanofibres, hybrid quantum systems, temperature, laser-cooled rubidium

(Some figures may appear in colour only in the online journal)

#### 1. Introduction

Optical nanofibres (ONFs) are ultrathin optical waveguides with sub-wavelength diameters [1] and have been used

Original content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.





<sup>&</sup>lt;sup>5</sup> Current address: Centre for Quantum Technologies, National University of Singapore, 3 Science Drive 2, Singapore 117543.

<sup>&</sup>lt;sup>6</sup> Current address: Department of Physics and Astronomy, Washington State University, Pullman, WA 99164, USA.

Author to whom any correspondence should be addressed.



Figure 1. Schematic of the experimental setup used for measuring the temperature of atoms near the surface of an optical nanofibre. APD: avalanche photodiode; ONF: optical nanofibre.



**Figure 2.** Measured transient absorption for different input probe powers through the ONF as the atom cloud is allowed to expand. Fluctuations in the background light level become dominant for measurements at the very low probe power of 0.03 nW.

recapture technique [16] and photon correlations [17]. Here, we present an alternative technique for temperature measurement based on the absorption of a probe beam. In contrast to the fluorescence-based measurements, this enables us to study the effect of the probe itself on the local temperature of the cloud and provides a method by which we can directly modify it. The ONF integrated into a magneto-optical trap (MOT) is used to measure the temperature of the atoms at the very central region of the atom cloud. Thence, we study the effect of a resonant probe beam on the local temperature of the atoms, i.e. those atoms closest to the nanofibre surface, and show a good fit with theory. Atoms coupled to ONFs could be used for preparing fibre-coupled quantum nodes in quantum computing [18] and the studies presented herein provide significant advances in the understanding of the ONF-atom system.

#### 2. Fabrication of an optical nanofibre

There are various ways for fabricating ONFs including using a CO<sub>2</sub> laser [19], acid flow etching [20], flame-brushed heatand-pull technique [21], direct drawing from bulk material [22], self-modulated taper-drawing [23], an electric ceramic microheater [24] and electrospinning [25]. We prepared our ONFs using the 'heat-and-pull' technique [21]. Unjacketed, standard optical fibre, with a cladding diameter of 125  $\mu$ m and a core diameter between 4 and 10  $\mu$ m, is heated to a temperature between 1200 °C-1500 °C which is above the annealing temperature of silica. Hence, its viscosity is lowered sufficiently to allow deformation, while remaining below the softening temperature so that the glass does not sag under its own weight. Meanwhile, the fibre is pulled simultaneously at both ends using computer-controlled motors. This leads to a tapering of the original fibre and provides an ONF with a submicron waist diameter. ONFs for use with cold atoms must be prepared in a way that will ensure very high light transmission through the waist region (i.e. very low losses), therefore necessitating that the tapering process be adiabatic [26]. In other words, there should be no coupling from the fibre-guided mode under consideration (e.g. the fundamental, LP<sub>01</sub> mode) to other fibre-guided (or cladding) modes. In the experiments reported here, the diameter of the ONF is  $\sim$ 350 nm with a transmission of  $\sim$ 84% for 780 nm light when installed in the ultrahigh vacuum chamber needed for the MOT. At this diameter, only the fundamental mode can propagate through the ONF for 780 nm light.

### 3. Temperature measurements using transient absorption

The ONF is installed in the MOT chamber and details of the method are described elsewhere [15]. A schematic of the experimental setup is shown in figure 1. A standard MOT arrangement is used for cooling the <sup>87</sup>Rb atoms [14] and the atom cloud is aligned with the ONF by monitoring coupled fluorescence through one of the fibre pigtails. A 780 nm probe beam locked to the  $5S_{1/2} F = 2 \rightarrow 5P_{3/2} F' = 3$  transition is sent through the ONF and interacts with the cold atoms around the waist. The transmission of the probe beam is collected on an avalanche photodiode and subsequently amplified using a low-noise amplifier before being displayed on an oscilloscope. The average temperature of atoms in a MOT can be measured using a transient absorption technique [27]. After trapping the atoms, the MOT beams are switched off and the atom cloud freely expands. As a consequence, absorption of the probe beam passing through the ONF reduces (i.e. its transmission through the fibre increases) since the number of atoms interacting with the evanescent field decreases as a function of the reduction of the atom cloud density during the expansion phase. The time evolution of the absorption signal can be used to characterise the average temperature of the atoms interacting with the evanescent field. Transient absorption measurements were made for various input probe powers, ranging from



Figure 3. Transient absorption with theoretical fits for various probe powers. The corresponding temperature values found from the fits are shown with the standard error obtained from the fitting parameters.

0.03 nW to 46 nW. From figure 2, we see that the maximum percentage absorption obtained for an unexpanded cloud reduces with power.

To determine the temperature of the atoms from the transient absorption signals, let us first assume that the cloud of atoms has a Gaussian density distribution at some initial time, t < 0, and expands ballistically once the trapping beams are switched off at t = 0. Thence, the density distribution,  $\rho(r, t)$ , evolves as [27]

$$\rho(r,t) = A(t)e^{-r^2/(w_0^2 + \bar{v}^2 t^2)},\tag{1}$$

where *r* is the radial coordinate,  $w_0$  is the initial Gaussian waist of the cloud,  $\bar{v}$  is the average thermal velocity of the atoms and A(t) is the peak density at a time, *t*, given by

$$A(t) = N / [\pi (w_0^2 + \bar{v}^2 t^2)]^{3/2}, \qquad (2)$$

where N is the total number of atoms in the trap.

The density of the atom cloud, in the region close to the fibre surface, is perturbed by the presence of the ONF [28]. This is due to finite radius of the ONF which produces shadowing around it. Atoms are less likely to enter this shadow region. Also, atoms colliding with the fibre are either adsorbed or expelled with a high kinetic energy. The amount of shadowing at a radial distance, r, from the fibre surface is determined by a quantity  $\alpha/\pi$ , where  $\alpha$  is given by  $\arcsin(a/r)$  for an ONF of radius a. This effect is

incorporated by approximating the atomic cloud density as [28]

$$\rho_{\rm ONF}(r,t) = \frac{N e^{-r^2/(w_0^2 + \bar{v}^2 t^2)}}{\pi^{3/2} (w_0^2 + \bar{v}^2 t^2)^{3/2}} \bigg[ 1 - \frac{\arcsin(a/r)}{\pi} \bigg].$$
(3)

According to Beers law, the differential change in the intensity of a probe passing through an absorbing medium is given by

$$dI = -\sigma_a \rho I(r) dr, \qquad (4)$$

where  $\sigma_a$  is the absorption cross-section,  $\rho$  is the density and I(r) is the field intensity at a radial distance, r. Looking at the transient behaviour of the absorption during free expansion at various powers (figure 2), we can estimate the temperature change of the cloud locally near the ONF due to the presence of the probe beam. The extension of the evanescent field from the fibre surface is very small (typically < 100 nm) compared to the diameter of the cloud (~1 mm) and, therefore, the probe beam is only expected to influence atoms in the evanescent field region. Fitting the transient absorption curves with equation (4) provides a value for  $\bar{\nu}$  for which the corresponding temperature can be determined from  $T = M\bar{\nu}^2/3k_B$ .

Figure 3 shows the normalised transient absorption spectra from figure 2 and the theoretical fittings, from which we can determine the average local temperature of the atoms in the interaction region (see figure 4). The effect of probe power on



**Figure 4.** Temperature measured by the transient absorption technique with a probe propagating through the ONF. The solid line shows an exponential fit. The error bars associated with the temperature values (as estimated from the fitting parameters in figure 3) are not visible on the scale of the data points.

temperature is evident. The average temperature of the cloud is measured to be 160  $\mu$ k when no probe beam propagates through the ONF and is measured by taking fluorescence images of the cloud with a CCD camera during ballistic expansions for various expansion times. The minimum probe power of 30 pW provides a temperature close to this average temperature, i.e. 180  $\mu$ K as opposed to 160  $\mu$ K with no probe present. This is expected, since the low power probe should have a minimal heating effect on the atoms. As the probe beam power is increased, the probe beam intensity in the evanescent field region increases; hence, the random recoils of the atoms due to the probe light gets increased leading to a local heating effect. The temperature increases as a function of the probe power and reaches a maximum value (figure 4) for the saturation of absorption of the atoms.

#### 4. Conclusion

We have measured the temperature of cold atoms using a transient absorption method whereby an on-resonant probe beam is passed through an optical nanofibre. The effect of the probe beam on the local temperature of the atoms shows the significant influence of probe intensity. This result is crucial since probe light is regularly passed through ONFs to confirm the presence of atoms in nanofibre-based traps [29, 30] and the detection technique clearly has an impact on the atom cloud parameters. We have observed an increase in the local temperature with probe power until saturation was reached. It should be noted that saturation effects due to the probe beam may affect the temperature measurements. In future work, it would be desirable to use a separate, very weak measurement beam to measure the temperature influence of the stronger probe beam. Furthermore, it is well-known that the temperature of a cold atom cloud is not uniform [31]; using our method, it should be possible to spatially map the temperature of the cloud by moving the nanofibre in a radial direction from the centre. This work could have implications on the dynamics of cold atoms in an ONF-cold atom system [5]. A recent proposal on quantum nondemolition measurements and spin squeezing using the dispersive response of nanofibretrapped atoms [32] relies on measuring the intensity and polarisation of the guided probe light and our work emphasises the importance of using ultralow probe powers, well below any saturation limits.

#### Acknowledgments

This work was funded by Okinawa Institute of Science and Technology Graduate University.

#### References

- Tong L, Gattass R R, Ashcom J B, He S, Lou J, Shen M, Maxwell I and Mazur E 2003 Subwavelength-diameter silica wires for low-loss optical wave guiding *Nature* 426 816–9
- [2] Morrissey M J, Deasy K, Frawley M, Kumar R, Prel E, Russell L, Truong V G and Nic Chormaic S 2013 Spectroscopy, manipulation and trapping of neutral atoms, molecules, and other particles using optical nanofibers: a review *Sensors* 13 10449–81
- [3] Nieddu T, Gokhroo V and Nic Chormaic S 2016 Optical nanofibres and neutral atoms J. Opt. 18 053001
- [4] Kumar R, Gokhroo V, Deasy K and Nic Chormaic S 2015 Autler–Townes splitting via frequency up-conversion at ultralow-power levels in cold <sup>87</sup>Rb atoms using an optical nanofiber *Phys. Rev.* A 91 053842
- [5] Gouraud B, Maxein D, Nicolas A, Morin O and Laurat J 2015 Demonstration of a memory for tightly guided light in an optical nanofiber *Phys. Rev. Lett.* **114** 180503
- [6] Jones D, Franson J and Pittman T 2015 Ladder-type electromagnetically induced transparency using nanofiberguided light in a warm atomic vapor *Phys. Rev.* A 92 043806
- [7] Kumar R, Gokhroo V and Nic Chormaic S 2015 Multi-level cascaded electromagnetically induced transparency in cold atoms using an optical nanofibre interface *New J. Phys.* 17 123012
- [8] Sayrin C, Clausen C, Albrecht B, Schneeweiss P and Rauschenbeutel A 2015 Storage of fiber-guided light in a nanofiber-trapped ensemble of cold atoms *Optica* 2 353–6
- [9] Nayak K, Melentiev P, Morinaga M, Kien F L, Balykin V and Hakuta K 2007 Optical nanofiber as an efficient tool for manipulating and probing atomic fluorescence *Opt. Express* 15 5431–8
- [10] Morrissey M J, Deasy K, Wu Y, Chakrabarti S and Nic Chormaic S 2009 Tapered optical fibers as tools for probing magneto-optical trap characteristics *Rev. Sci. Instrum.* 80 053102
- [11] Russell L, Kumar R, Tiwari V B and Nic Chormaic S 2014 Investigation of a <sup>85</sup>Rb dark magneto-optical trap using an optical nanofibre *Meas. Sci. Technol.* 25 055203
- [12] Sagué G, Vetsch E, Alt W, Meschede D and Rauschenbeutel A 2007 Cold-atom physics using ultrathin optical fibers: lightinduced dipole forces and surface interactions *Phys. Rev. Lett.* 99 163602

- [13] Dawkins S, Mitsch R, Reitz D, Vetsch E and Rauschenbeutel A 2011 Dispersive optical interface based on nanofiber-trapped atoms *Phys. Rev. Lett.* **107** 243601
- [14] Kumar R, Gokhroo V, Deasy K, Maimaiti A, Frawley M C, Phelan C and Nic Chormaic S 2015 Interaction of lasercooled <sup>87</sup>Rb atoms with higher order modes of an optical nanofibre *New J. Phys.* **17** 013026
- [15] Russell L, Deasy K, Daly M J, Morrissey M J and Nic Chormaic S 2012 Sub-Doppler temperature measurements of laser-cooled atoms using optical nanofibres *Meas. Sci. Technol.* 23 015201
- [16] Russell L, Kumar R, Tiwari V B and Nic Chormaic S 2013 Measurements on release-recapture of cold <sup>85</sup>Rb atoms using an optical nanofibre in a magneto-optical trap *Opt. Commun.* 309 313–7
- [17] Grover J, Solano P, Orozco L and Rolston S 2015 Photoncorrelation measurements of atomic-cloud temperature using an optical nanofiber *Phys. Rev.* A 92 013850
- [18] Kimble H J 2008 The quantum internet Nature 453 1023–30
- [19] Ward J M, OShea D G, Shortt B J, Morrissey M J, Deasy K and Chormaic S Nic 2006 Heat-and-pull rig for fiber taper fabrication *Rev. Sci. Instrum.* 77 083105
- [20] Zhang E J, Sacher W D and Poon J K 2010 Hydrofluoric acid flow etching of low-loss subwavelength-diameter biconical fiber tapers *Opt. Express* 18 22593–8
- [21] Ward J, Maimaiti A, Le V H and Nic Chormaic S 2014 Contributed review: optical micro-and nanofiber pulling rig *Rev. Sci. Instrum.* 85 111501
- [22] Tong L, Hu L, Zhang J, Qiu J, Yang Q, Lou J, Shen Y, He J and Ye Z 2006 Photonic nanowires directly drawn from bulk glasses *Opt. Express* 14 82–7
- [23] Tong L, Lou J, Ye Z, Svacha G T and Mazur E 2005 Selfmodulated taper drawing of silica nanowires *Nanotechnology* 16 1445

- [24] Sørensen H L, Polzik E S and Appel J 2014 Heater selfcalibration technique for shape prediction of fiber tapers *J. Lightwave Technol.* 32 1886–91
- [25] Liu H, Edel J B, Bellan L M and Craighead H 2006
  Electrospun polymer nanofibers as subwavelength optical waveguides incorporating quantum dots *Small* 2 495–9
- [26] Love J, Henry W, Stewart W, Black R, Lacroix S and Gonthier F 1991 Tapered single-mode fibres and devices: I. Adiabaticity criteria *IEE Proc.* J 138 343–54
- [27] Silva R, Magalhães K M F, Henn E A d L, Marcassa L G and Bagnato V S 2006 Temperature determination for magneto optical trapped atoms using a single parameter transient absorption *Opt. Commun.* 265 526–31
- [28] Sagué G 2008 Cold atom physics using ultra-thin optical fibres *PhD Thesis*, Rheinischen Freidrich-Wilhelms-Universität, Bonn
- [29] Vetsch E, Reitz D, Sagué G, Schmidt R, Dawkins S and Rauschenbeutel A 2010 Optical interface created by laser-cooled atoms trapped in the evanescent field surrounding an optical nanofiber *Phys. Rev. Lett.* **104** 203603
- [30] Goban A, Choi K, Alton D, Ding D, Lacroûte C, Pototschnig M, Thiele T, Stern N and Kimble H 2012 Demonstration of a state-insensitive, compensated nanofiber trap *Phys. Rev. Lett.* **109** 033603
- [31] Arnold A and Manson P 2000 Atomic density and temperature distributions in magneto-optical traps J. Opt. Soc. B 17 497–506
- [32] Qi X, Baragiola B Q, Jessen P S and Deutsch I H 2016 Dispersive response of atoms trapped near the surface of an optical nanofiber with applications to quantum nondemolition measurement and spin squeezing *Phys. Rev.* A 93 023817